

Weicon GmbH

Revision date: 21.03.2010

Revision no.:

1,00

Casting Resin MS 1000, Resin

7619-0215

1. Identification of the substance/preparation and of the company/undertaking**Identification of the substance or preparation**

Casting Resin MS 1000, Resin

Further trade names

10520-2

Use of the substance/preparation

Adhesive

Company/undertaking identification**Manufacturer**

Weicon GmbH

Königsberger Straße 255

D-48157 Münster

Telephone: +49 (0) 251 9322 - 0

Telefax: +49 (0) 251 9322 - 244

e-mail: info@weicon.de

Internet: www.weicon.de

Responsible for the safety data sheet: sds@gbk-ingelheim.de

Supplier

WEICON Inc.

20 Steckle Place, Unit 20

Kitchener, Ontario N2E 2C3

Telephone: 519 896 5252

Telefax: 519 896 5254

e-mail: info@weicon.ca

Emergency telephone number: 0 11 49 178 433 74 34 (CONSULTANK Lutz Harder GmbH)

2. Hazards identification**Classification**

Indications of danger : Irritant, Dangerous for the environment

R-phrases:

Irritating to eyes and skin.

May cause sensitization by skin contact.

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

3. Composition/information on ingredients**Chemical characterization (Mixture)**

2-Component Epoxy Resins

Modified bisphenol-A-epoxy resin.

Hazardous components

CAS-No.	Chemical name	Quantity
25068-38-6	epoxy resin (number average molecular weight <= 700), reaction product: bisphenol-A-(epichlorhydrin)	70 - 82 %

4. First aid measures**General information**

Remove contaminated soaked clothing immediately.

In the event of persistent symptoms receive medical treatment.

After inhalation

Move to fresh air in case of accidental inhalation of vapours or decomposition products.

Weicon GmbH

Revision date: 21.03.2010

Revision no.:

1,00

Casting Resin MS 1000, Resin

7619-0215

In the event of symptoms refer for medical treatment.

After contact with skin

Wash off immediately with soap and plenty of water.

Consult a doctor if skin irritation persists.

After contact with eyes

Rinse eyes immediately with large amounts of water for several minutes, especially under the eyelids.

Seek medical treatment by eye specialist.

After ingestion

Administer activated charcoal.

Do not induce vomiting.

Rinse out mouth and give plenty of water to drink.

Give plenty of water to drink in small sips.

Advice to doctor

In the event of pulmonary irritation treat initially with dexamethasone metered-dose aerosol.

5. Fire-fighting measures

Suitable extinguishing media

Foam, carbon dioxide (CO₂), dry chemical, water-spray.

Extinguishing media which must not be used for safety reasons

Full water jet

Special exposure hazards arising from substance or preparation itself, combustion products, resulting gases

Fire may produce:

Carbon monoxide (CO)

Carbon dioxide (CO₂)

Dense black smoke

Special protective equipment for fire-fighters

A self contained breathing apparatus should be worn in fire conditions.

Additional information

Burns down under strong soot production.

Collect contaminated firefighting water separately, must not be discharged into the drains.

6. Accidental release measures

Personal precautions

Use personal protective clothing.

In case of vapour formation use respirator.

Ensure adequate ventilation.

Environmental precautions

Clean contaminated surface thoroughly.

Do not discharge into the drains/surface waters/groundwater.

Do not discharge into the subsoil/soil.

Methods for cleaning up/taking up

Take up with absorbent material (e.g. sand, kieselguhr, acid binder, general-purpose binder, sawdust).

Shovel into suitable container for disposal.

7. Handling and storage

Handling

Advice on safe handling

Keep in closed original container.

Use only in thoroughly ventilated areas.

Avoid contact with skin, eyes and clothing.

When using, do not eat, drink or smoke.

Weicon GmbH

Revision date: 21.03.2010

Revision no.:

1,00

Casting Resin MS 1000, Resin

7619-0215

Advice on protection against fire and explosion

No special protective measures against fire required.
Pay attention to general rules of internal fire prevention.
Take precautionary measures against static discharges.

Further information on handling

Open and handle container with care.

Storage**Requirements for storage rooms and vessels**

Keep container tightly closed in a dry, cool and well-ventilated place.
Protect from direct solar radiation.
Protect from heat/overheating.

Advice on storage compatibility

Do not store together with animal feedstuffs.
Do not store together with food.

Further information on storage conditions

Storage temperature between 2°C to 40°C.

Storageclass (VCI): _____ 13

8. Exposure controls/personal protection**Exposure limit values****Additional advice on limit values**

Contains epoxy compounds. Observe the instructions of the manufacturer

Occupational exposure controls

Ensure adequate ventilation, especially in confined areas.

Protective and hygiene measures

Do not inhale vapours.
Wash hands before breaks and immediately after handling the product.
When using, do not eat, drink or smoke.
Avoid contact with skin, eyes and clothing.
Remove and wash contaminated clothes before re-use.

Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A).

Hand protection

Protective gloves resistant to chemicals made of butyl, Minimum coat thickness 0,7 mm, Permeation resistance (wear duration) approx. 480 minutes, i.e. protective glove <Butoject 898> made by www.kcl.de. This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.
Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Eye protection

Tightly fitting goggles

Skin protection

Light protective clothing

9. Physical and chemical properties**General information**

Physical state: Liquid
Colour: Light yellow
Odour: Hardly noticeable

Weicon GmbH

Revision date: 21.03.2010

Revision no.:

1,00

Casting Resin MS 1000, Resin

7619-0215

Important health, safety and environmental information

	Test method
pH-Value (at 20 °C):	approx. 7 1:1 in water
Changes in the physical state	
Boiling point:	>200 °C
Flash point:	>200 °C DIN 51758
Vapour pressure: (at 25 °C)	<0,1 hPa
Density (at 25 °C):	1,1 g/cm ³ DIN 51757
Water solubility: (at 20 °C)	Insoluble
Viscosity / dynamic: (at 25 °C)	1250 - 1600 mPa·s

10. Stability and reactivity**Conditions to avoid**

To avoid thermal decomposition, do not overheat.

Thermal decomposition >200°C

Materials to avoid

Reactions with strong oxidizing agents.

Hazardous decomposition products

Carbon monoxide and carbon dioxide.

Risk of formation of toxic pyrolysis products.

Additional information

No decomposition if stored and applied as directed.

11. Toxicological information**Acute toxicity**

LD50/oral = >5000 mg/kg Rat

Corrosive and irritant effects

Skin irritation: Irritant Rabbit

Eye irritation : Irritant Rabbit eye

Sensitizing effects

Sensitization through skin contact possible.

Sensitization skin (guinea pig): Sensitizing

Empirical data on effects on humans

If appropriately handled and if in accordance with the general hygienic rules, no damages to health have become known.

12. Ecological information**Further information**

Do not discharge product unmonitored into the environment.

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Product is not allowed to be discharged into aquatic environment.

13. Disposal considerations**Advice on disposal**

Remove in accordance with local official regulations.

Uncontaminated packaging may be treated as household waste.

Packaging that cannot be cleaned should be disposed of like the product.

Contaminated packaging

Empty containers should be taken for local recycling, recovery or waste disposal.

Weicon GmbH

Revision date: 21.03.2010

Revision no.:

1,00

Casting Resin MS 1000, Resin

7619-0215

Contaminated packagings are to be treated like the product itself.

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

14. Transport information

Canadian TDG

Proper shipping name

Environmentally hazardous substance, liquid, n.o.s. (Bisphenol A Epoxy Resin)

UN/ID number: 3088

Hazard classes: 9

Packing group: III

Hazard label: 9

Land transport (ADR/RID)

UN number: 3082

ADR/RID class: 9

Classification Code: M7

Warning plate

Hazard-no.: 90

Hazard label: 9



ADR/RID packing group: III

Limited quantity: LQ27

Description of the goods

Environmentally hazardous substance, liquid, n.o.s. (Bisphenol A Epoxy Resin)

Other applicable information (land transport)

Transport category: 3

Tunnel restriction code: E

Additional label with symbol "fish and tree" according to subsection 5.2.1.8.3. ADR for single packagings and inner packagings with > 5 kg or 5 L.

Marine transport

UN number: 3082

IMDG code: 9

Marine pollutant: P

Hazard label: 9



IMDG packing group: III

Description of the goods

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (cont. epoxy resin)

Other applicable information (marine transport)

Additional label with symbol "fish and tree" according to subsection 5.2.1. IMDG Code for single packagings and inner packagings with > 5 kg or 5 L.

Air transport

UN/ID number: 3082

ICAO/IATA-DGR: 9

Hazard label: 9

Weicon GmbH

Revision date: 21.03.2010

Revision no.:

1,00

Casting Resin MS 1000, Resin

7619-0215



ICAO packing group:

III

Description of the goods

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (cont. epoxy resin)

Other applicable information (air transport)

Additional label with symbol "fish and tree" according to subsection 7.1.6.3. IATA/DGR for single packagings and inner packagings with > 5 kg or 5 L.

15. Regulatory information

Canadian regulations

DSL/NDSL inventory status

All of the components are listed on the DSL Inventory.

WHMIS classification

WHMIS: D2B

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all information required by the CPR.

16. Other information

Other data

Data of sections 4 to 8, as well as 10 to 12, do not necessarily refer to the use and the regular handling of the product (in this sense consult package leaflet and expert information), but to release of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product (s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

"(n.a. = not applicable; n.d. = not determined)"

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)