

Weicon GmbH

Revision date: 16.10.2009

Revision no.:

1,00

Easy-Mix N 50 resin

7619-0003

1. Identification of the substance/preparation and of the company/undertaking**Identification of the substance or preparation**

Easy-Mix N 50 resin

Further trade names

10650-2

Use of the substance/preparation

Adhesive

Company/undertaking identification**Manufacturer**

Weicon GmbH

Königsberger Straße 255

D-48157 Münster

Telephone: +49 (0) 251 9322 - 0

Telefax: +49 (0) 251 9322 - 244

e-mail: info@weicon.de

Internet: www.weicon.de

Responsible for the safety data sheet: sds@gbk-ingelheim.de

Supplier

WEICON Inc.

20 Steckle Place, Unit 20

Kitchener, Ontario N2E 2C3

Telephone: 519 896 5252

Telefax: 519 896 5254

e-mail: info@weicon.ca

Emergency telephone number: 0 11 49 178 433 74 34 (CONSULTANK Lutz Harder GmbH)

2. Hazards identification**Classification**

Indications of danger : Irritant, Dangerous for the environment

R-phrases:

Irritating to eyes and skin.

May cause sensitization by skin contact.

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

3. Composition/information on ingredients**Chemical characterization (Mixture)**

Resin for a two-component epoxy adhesive.

Hazardous components

CAS-No.	Chemical name	Quantity
25068-38-6	epoxy resin (number average molecular weight <= 700), reaction product: bisphenol-A-(epichlorhydrin)	50 -100 %

4. First aid measures**General information**

Remove contaminated soaked clothing immediately.

In the event of persistent symptoms receive medical treatment.

After inhalation

Move to fresh air in case of accidental inhalation of vapours or decomposition products.

In the event of symptoms refer for medical treatment.

Weicon GmbH

Revision date: 16.10.2009

Revision no.:

1,00

Easy-Mix N 50 resin

7619-0003

After contact with skin

Wash off immediately with soap and plenty of water.

Consult a doctor if skin irritation persists.

After contact with eyes

Rinse eyes immediately with large amounts of water for several minutes, especially under the eyelids.

Seek medical treatment by eye specialist.

After ingestion

Summon a doctor immediately.

Advice to doctor

In the event of pulmonary irritation treat initially with dexamethasone metered-dose aerosol.

5. Fire-fighting measures

Suitable extinguishing media

Foam, carbon dioxide (CO₂), dry chemical, water-spray.

Extinguishing media which must not be used for safety reasons

Full water jet

Special exposure hazards arising from substance or preparation itself, combustion products, resulting gases

Fire may produce:

Carbon monoxide (CO)

Carbon dioxide (CO₂)

Special protective equipment for fire-fighters

A self contained breathing apparatus should be worn in fire conditions.

Additional information

Cool containers at risk with water spray jet.

6. Accidental release measures

Personal precautions

Use personal protective clothing.

In case of vapour formation use respirator.

Ensure adequate ventilation.

Environmental precautions

Clean contaminated surface thoroughly.

Do not discharge into the drains/surface waters/groundwater.

Methods for cleaning up/taking up

Take up with absorbent material.

Shovel into suitable container for disposal.

7. Handling and storage

Handling

Advice on safe handling

Keep in closed original container.

Use only in thoroughly ventilated areas.

Avoid contact with skin, eyes and clothing.

When using, do not eat, drink or smoke.

Advice on protection against fire and explosion

No special protective measures against fire required.

Pay attention to general rules of internal fire prevention.

Storage

Requirements for storage rooms and vessels

Keep container tightly closed in a dry, cool and well-ventilated place.

Weicon GmbH

Revision date: 16.10.2009

Revision no.:

1,00

Easy-Mix N 50 resin

7619-0003

Advice on storage compatibility

Incompatible with:

Oxidizing agents, Amines, Acids and bases.

Further information on storage conditions

Do not store together with animal feedstuffs.

Do not store together with food.

Storageclass (VCI): 13

8. Exposure controls/personal protection**Exposure limit values****Additional advice on limit values**

Contains epoxy compounds. Observe the instructions of the manufacturer

Occupational exposure controls

Ensure adequate ventilation, especially in confined areas.

Protective and hygiene measures

Do not inhale vapours.

Wash hands before breaks and immediately after handling the product.

When using, do not eat, drink or smoke.

Avoid contact with skin, eyes and clothing.

Remove and wash contaminated clothes before re-use.

Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A).

Hand protection

Protective gloves resistant to chemicals made off natural-rubber latex, Minimum coat thickness 0.6 mm, Permeation resistance (wear duration) approx. 480 minutes, i.e. protective glove <Lapren 706> made by www.kcl.de.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Eye protection

Tightly fitting goggles

Skin protection

Long sleeved clothing.

9. Physical and chemical properties**General information**

Physical state:	Pasty
Colour:	Yellow
Odour:	Hardly noticeable

Important health, safety and environmental information

Test method

Changes in the physical state

Flash point:	>100 °C
Density (at 20 °C):	1,16 g/cm ³
Water solubility: (at 20 °C)	Insoluble

10. Stability and reactivity

Weicon GmbH

Revision date: 16.10.2009

Revision no.:

1,00

Easy-Mix N 50 resin

7619-0003

Conditions to avoid

To avoid thermal decomposition, do not overheat.

Keep away from heat.

Materials to avoid

Reactions with strong acids and alkalis.

Reactions with strong oxidizing agents.

Hazardous decomposition products

Carbon monoxide and carbon dioxide.

Additional information

No decomposition if stored and applied as directed.

11. Toxicological information**Corrosive and irritant effects**

Skin irritation (rabbit): Irritant

Eye irritation (rabbit): Irritant

Sensitizing effects

Sensitization through skin contact possible.

Sensitization skin (guinea pig): Sensitizing

Empirical data on effects on humans

If appropriately handled and if in accordance with the general hygienic rules, no damages to health have become known.

12. Ecological information**Further information**

Do not flush into surface water or sanitary sewer system.

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

13. Disposal considerations**Advice on disposal**

Remove in accordance with local official regulations.

Uncontaminated packaging may be treated as household waste.

Contaminated packaging

Empty containers should be taken for local recycling, recovery or waste disposal.

Contaminated packagings are to be treated like the product itself.

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

14. Transport information**Canadian TDG****Proper shipping name**

Environmentally hazardous substance, solid, n.o.s. (Bisphenol A Epoxy Resin)

UN/ID number: 3077

Hazard classes: 9

Packing group: III

Hazard label: 9

Land transport (ADR/RID)

UN number: 3077

ADR/RID class: 9

Classification Code: M7

Warning plate

Hazard-no.: 90

Weicon GmbH

Revision date: 16.10.2009

Revision no.:

1,00

Easy-Mix N 50 resin

7619-0003

Hazard label: 9

ADR/RID packing group: III
Limited quantity: LQ27**Description of the goods**

Environmentally hazardous substance, solid, n.o.s. (Bisphenol A Epoxy Resin)

Other applicable information (land transport)

Transport category: 3

Tunnel restriction code: E

Additional label with symbol "fish and tree" according to subsection 5.2.1.8.3. ADR for single packagings and inner packagings with > 5 kg or 5 L.

Marine transportUN number: 3077
IMDG code: 9
Marine pollutant: P
Hazard label: 9

IMDG packing group: III

Description of the goods

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (cont. epoxy resin)

Other applicable information (marine transport)

Additional label with symbol "fish and tree" according to subsection 5.2.1. IMDG Code for single packagings and inner packagings with > 5 kg or 5 L.

Air transportUN/ID number: 3077
ICAO/IATA-DGR: 9
Hazard label: 9

ICAO packing group: III

Description of the goods

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (cont. epoxy resin)

Other applicable information (air transport)

Additional label with symbol "fish and tree" according to subsection 7.1.6.3. IATA/DGR for single packagings and inner packagings with > 5 kg or 5 L.

15. Regulatory information**Canadian regulations****DSL/NDSL inventory status**

All of the components are listed on the DSL Inventory.

WHMIS classification

WHMIS: D2B

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all information required by the CPR.

Weicon GmbH

Revision date: 16.10.2009

Revision no.:

1,00

Easy-Mix N 50 resin

7619-0003

16. Other information

Other data

Data of sections 4 to 8, as well as 10 to 12, do not necessarily refer to the use and the regular handling of the product (in this sense consult package leaflet and expert information), but to release of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product (s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

"(n.a. = not applicable; n.d. = not determined)"

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)