

Weicon GmbH

Revision date: 12.12.2009

Revision no.:

1,00

Fast-Metal Minute Adhesive Resin/Hardener

7619-0097

1. Identification of the substance/preparation and of the company/undertaking**Identification of the substance or preparation**

Fast-Metal Minute Adhesive Resin/Hardener

Further trade names

10655-1/2

Use of the substance/preparation

Adhesive

Company/undertaking identification**Manufacturer**

Weicon GmbH

Königsberger Straße 255

D-48157 Münster

Telephone: +49 (0) 251 9322 - 0

Telefax: +49 (0) 251 9322 - 244

e-mail: info@weicon.de

Internet: www.weicon.de

Responsible for the safety data sheet: sds@gbk-ingelheim.de

Supplier

WEICON Inc.

20 Steckle Place, Unit 20

Kitchener, Ontario N2E 2C3

Telephone: 519 896 5252

Telefax: 519 896 5254

e-mail: info@weicon.ca

Emergency telephone number: 0 11 49 178 433 74 34 (CONSULTANK Lutz Harder GmbH)

2. Hazards identification**Classification**

Indications of danger : Irritant, Dangerous for the environment

R-phrases:

Irritating to eyes and skin.

May cause sensitization by skin contact.

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

3. Composition/information on ingredients**Chemical characterization (Mixture)**

Resin for a two-component epoxy adhesive.

Hardener for a 2-component epoxy adhesive

Hazardous components

CAS-No.	Chemical name	Quantity
25068-38-6	epoxy resin (number average molecular weight <= 700), reaction product: bisphenol-A-(epichlorhydrin)	10 - 24 %
68609-97-2	oxirane, mono[(C12-14-alkyloxy)methyl] derivs.	1 - 10 %
9003-36-5	Epoxidharz	1 - 10 %
28064-14-4	Reaktionsprodukt: Bisphenol-F-Epichlorhydrinharze mit durchschnittlichem Molekulargewicht <= 700	1 - 10 %
52338-87-1	1,3-bis[3-(dimethylamino)propyl]urea	1 - 9 %

4. First aid measures

General information

Remove contaminated soaked clothing immediately.
In the event of persistent symptoms receive medical treatment.

After inhalation

Move to fresh air in case of accidental inhalation of vapours or decomposition products.
In the event of symptoms refer for medical treatment.

After contact with skin

Wash off immediately with soap and plenty of water.
Consult a doctor if skin irritation persists.

After contact with eyes

Rinse eyes immediately with large amounts of water for several minutes, especially under the eyelids.
Seek medical treatment by eye specialist.

After ingestion

Do not induce vomiting.
Summon a doctor immediately.
Rinse out mouth thoroughly with water.

5. Fire-fighting measures

Suitable extinguishing media

Alcohol-resistant foam, dry chemical, carbon dioxide (CO₂), water-spray.

Extinguishing media which must not be used for safety reasons

Full water jet

Special exposure hazards arising from substance or preparation itself, combustion products, resulting gases

Fire may produce:

Carbon monoxide (CO)
Carbon dioxide (CO₂)
Nitrogen oxides (NO_x)

Special protective equipment for fire-fighters

A self contained breathing apparatus should be worn in fire conditions.

Additional information

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

6. Accidental release measures

Personal precautions

Use personal protective clothing.
In case of vapour formation use respirator.
Ensure adequate ventilation.
Keep away sources of ignition.

Environmental precautions

Clean contaminated surface thoroughly.
Do not discharge into the drains/surface waters/groundwater.
Do not discharge into the subsoil/soil.

Methods for cleaning up/taking up

Take up with absorbent material.
Shovel into suitable container for disposal.

7. Handling and storage

Handling

Advice on safe handling

Keep in closed original container.
Use only in thoroughly ventilated areas.

Weicon GmbH

Revision date: 12.12.2009

Revision no.:

1,00

Fast-Metal Minute Adhesive Resin/Hardener

7619-0097

Avoid contact with skin, eyes and clothing.

When using, do not eat, drink or smoke.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharges.

Pay attention to general rules of internal fire prevention.

Storage

Requirements for storage rooms and vessels

Keep container tightly closed in a dry, cool and well-ventilated place.

Protect from heat/overheating.

Protect from direct solar radiation.

Further information on storage conditions

Do not store together with animal feedstuffs.

Storageclass (VCI):

13

8. Exposure controls/personal protection

Exposure limit values

Additional advice on limit values

Contains epoxy compounds. Observe the instructions of the manufacturer

Occupational exposure controls

Ensure adequate ventilation, especially in confined areas.

Protective and hygiene measures

Do not inhale gases/vapours/aerosols.

Wash hands before breaks and immediately after handling the product.

When using, do not eat, drink or smoke.

Avoid contact with skin, eyes and clothing.

Remove and wash contaminated clothes before re-use.

Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A).

Hand protection

Protective gloves resistant to chemicals made off natural-rubber latex, Minimum coat thickness 0.6 mm, Permeation resistance (wear duration) approx. 480 minutes, i.e. protective glove <Lapren 706> made by www.kcl.de.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Eye protection

Tightly fitting goggles

Skin protection

Protective clothing

9. Physical and chemical properties

General information

Physical state:

Pasty

Colour:

Various, depending on coloration

Odour:

Perceptible

Important health, safety and environmental information

Test method

Changes in the physical state

Weicon GmbH

Revision date: 12.12.2009

Revision no.:

1,00

Fast-Metal Minute Adhesive Resin/Hardener

7619-0097

Flash point:	>200 °C	DIN 51758
Density:	1,1 g/cm ³	
Water solubility: (at 20 °C)	Difficult to dissolve	

10. Stability and reactivity

Conditions to avoid

To avoid thermal decomposition, do not overheat.
Keep away from heat.

Materials to avoid

Reactions with strong acids and alkalis.
Reactions with strong oxidizing agents.

Hazardous decomposition products

Carbon monoxide and carbon dioxide.
Nitrous oxides (NO_x)
Risk of formation of toxic pyrolysis products.

Additional information

No decomposition if stored and applied as directed.

11. Toxicological information

Corrosive and irritant effects

Skin irritation: Irritant Rabbit
Eye irritation : Irritant Rabbit eye

Sensitizing effects

Sensitization through skin contact possible.
Sensitization skin (guinea pig): Sensitizing

Empirical data on effects on humans

If appropriately handled and if in accordance with the general hygienic rules, no damages to health have become known.

12. Ecological information

Further information

Do not discharge product unmonitored into the environment.
Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Product is not allowed to be discharged into aquatic environment.

13. Disposal considerations

Advice on disposal

Remove in accordance with local official regulations.
Where possible recycling is preferred to disposal.
If recycling is not practicable, dispose of in compliance with local regulations.

Contaminated packaging

Empty containers should be taken for local recycling, recovery or waste disposal.
Contaminated packagings are to be treated like the product itself.
Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

14. Transport information

Canadian TDG

Proper shipping name

Environmentally hazardous substance, liquid, n.o.s. (Epoxy resin)

UN/ID number:	UN3082
Hazard classes:	9
Packing group:	III

Weicon GmbH

Revision date: 12.12.2009

Revision no.:

1,00

Fast-Metal Minute Adhesive Resin/Hardener

7619-0097

Hazard label: 9

Land transport (ADR/RID)

UN number: 3082

ADR/RID class: 9

Classification Code: M7

Warning plate

Hazard-no.: 90

Hazard label: 9



ADR/RID packing group: III

Limited quantity: LQ27

Description of the goods

Environmentally hazardous substance, liquid, n.o.s. (Epoxy resin)

Other applicable information (land transport)

Transport category: 3

Tunnel restriction code: E

Additional label with symbol "fish and tree" according to subsection 5.2.1.8.3. ADR for single packagings and inner packagings with > 5 kg or 5 L.

Marine transport

UN number: 3082

IMDG code: 9

Hazard label: 9



IMDG packing group: III

EmS: F-A; S-F

Limited quantity: 5 L / 30 kg

Description of the goods

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (cont. epoxy resin)

Other applicable information (marine transport)

Additional label with symbol "fish and tree" according to subsection 5.2.1. IMDG Code for single packagings and inner packagings with > 5 kg or 5 L.

Air transport

UN/ID number: 3082

ICAO/IATA-DGR: 9

Hazard label: 9



ICAO packing group: III

Limited quantity Passenger: Y914 / 30 kg G

IATA-packing instructions - Passenger: 914

IATA-max. quantity - Passenger: 450 L

IATA-packing instructions - Cargo: 914

IATA-max. quantity - Cargo: 450 L

Description of the goods

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (cont. epoxy resin)

Weicon GmbH

Revision date: 12.12.2009

Revision no.:

1,00

Fast-Metal Minute Adhesive Resin/Hardener

7619-0097

Other applicable information (air transport)

Additional label with symbol "fish and tree" according to subsection 7.1.6.3. IATA/DGR for single packagings and inner packagings with > 5 kg or 5 L.

15. Regulatory information

Canadian regulations

DSL/NDSL inventory status

All of the components are listed on the DSL Inventory.

WHMIS classification

WHMIS: D2B

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all information required by the CPR.

16. Other information

Other data

Data of sections 4 to 8, as well as 10 to 12, do not necessarily refer to the use and the regular handling of the product (in this sense consult package leaflet and expert information), but to release of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product (s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

"(n.a. = not applicable; n.d. = not determined)"

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)