

Weicon GmbH

Revision date: 15.12.2009

Revision no.:

1,00

Flex 310, Adhesive and Sealant, different colours

7619-0101

1. Identification of the substance/preparation and of the company/undertaking**Identification of the substance or preparation**

Flex 310, Adhesive and Sealant, different colours

Further trade names

13302

Use of the substance/preparation

Adhesive / Sealant

Company/undertaking identification**Manufacturer**

Weicon GmbH

Königsberger Straße 255

D-48157 Münster

Telephone: +49 (0) 251 9322 - 0

Telefax: +49 (0) 251 9322 - 244

e-mail: info@weicon.de

Internet: www.weicon.de

Responsible for the safety data sheet: sds@gbk-ingelheim.de

Supplier

WEICON Inc.

20 Steckle Place, Unit 20

Kitchener, Ontario N2E 2C3

Telephone: 519 896 5252

Telefax: 519 896 5254

e-mail: info@weicon.ca

Emergency telephone number: 0 11 49 178 433 74 34 (CONSULTANK Lutz Harder GmbH)

2. Hazards identification**Classification**

Indications of danger : Harmful

R-phrases:

May cause sensitization by inhalation.

3. Composition/information on ingredients**Chemical characterization (Mixture)**

1-Component Adhesives and Sealants. (Permanently elastic)

Hazardous components

CAS-No.	Chemical name	Quantity
1330-20-7	xylene	<5 %
90622-57-4	Alkanes, C9-12-iso-	<2 %
26447-40-5	methylenediphenyl diisocyanate	<1 %

4. First aid measures**General information**

Remove contaminated soaked clothing immediately.

In the event of persistent symptoms receive medical treatment.

If threatening unconsciousness, position and transport in recovery position.

After inhalation

Move to fresh air in case of accidental inhalation of vapours or decomposition products.

In the event of symptoms refer for medical treatment.

After contact with skin

Consult a doctor if skin irritation persists.

After contact with eyes

Rinse eyes immediately with large amounts of water for several minutes, especially under the eyelids.

Seek medical treatment by eye specialist.

After ingestion

Do not induce vomiting.

Call a physician immediately.

Advice to doctor

The following symptoms may occur: Shortness of breath

In the event of pulmonary irritation treat initially with dexamethasone metered-dose aerosol.

5. Fire-fighting measures

Suitable extinguishing media

Foam, carbon dioxide (CO₂), dry chemical, water-spray.

Special exposure hazards arising from substance or preparation itself, combustion products, resulting gases

Fire may produce:

Carbon monoxide (CO)

Carbon dioxide (CO₂)

Special protective equipment for fire-fighters

Use breathing apparatus with independent air supply.

Additional information

Collect contaminated firefighting water separately, must not be discharged into the drains.

6. Accidental release measures

Personal precautions

Remove persons to safety.

Ensure adequate ventilation.

Keep away sources of ignition.

Environmental precautions

Clean contaminated surface thoroughly.

Do not discharge into the drains or bodies of water.

Methods for cleaning up/taking up

Take up mechanically.

Shovel into suitable container for disposal.

7. Handling and storage

Handling

Advice on safe handling

Use only in thoroughly ventilated areas.

Avoid contact with skin, eyes and clothing.

Keep in closed original container.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

Vapours can form an explosive mixture with air.

Further information on handling

Open and handle container with care.

Storage

Requirements for storage rooms and vessels

Keep container tightly closed in a dry, cool and well-ventilated place.

Weicon GmbH

Revision date: 15.12.2009

Revision no.:

1,00

Flex 310, Adhesive and Sealant, different colours

7619-0101

Protect from frost.

Protect from heat and direct solar radiation.

Store in a dry place.

Further information on storage conditions

Storage stability 12 months maximum.

Storageclass (VCI): 13

8. Exposure controls/personal protection**Exposure limit values****Exposure limits (ACGIH)**

CAS No.	Substance	ppm	mg/m ³	F/ml	Category	Origin
1330-20-7	Xylene	100	434		TWA (8 h)	TLV
		150	651		STEL (15 min)	TLV
		-	-		Peak	TLV

Occupational exposure controls

Ensure adequate ventilation, especially in confined areas.

Do not inhale gases/vapours/aerosols.

Avoid contact with eyes and skin.

Keep away from food and drink.

Protective and hygiene measures

Wash hands before breaks and immediately after handling the product.

When using, do not eat, drink or smoke.

Avoid contact with skin, eyes and clothing.

Remove and wash contaminated clothes before re-use.

Respiratory protection

Use suitable breathing apparatus if there is inadequate ventilation.

Hand protection

Protective gloves resistant to chemicals made of butyl, Minimum coat thickness 0,7 mm, Permeation resistance (wear duration) approx. 480 minutes, i.e. protective glove <Butoject 898> made by www.kcl.de.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Eye protection

Safety goggles

Skin protection

Protective clothing

9. Physical and chemical properties**General information**

Physical state:

Pasty

Colour:

Various, depending on coloration

Odour:

Solvent-like

Important health, safety and environmental information

pH-Value:

Test method
n.d.**Changes in the physical state**

Flash point:

n.a.

Lower explosion limits:

0,4 vol. %

Weicon GmbH

Revision date: 15.12.2009

Revision no.:

1,00

Flex 310, Adhesive and Sealant, different colours

7619-0101

Upper explosion limits: 7,6 vol. %

Vapour pressure: <100 hPa hPa
(at 20 °C)

Density (at 20 °C): 1,175 g/cm³

Water solubility: Insoluble, Reacts with water
(at 20 °C)

Solvent content

5,9%

Other information

Ignition temperature: >200 °C

10. Stability and reactivity**Conditions to avoid**

Reactions with water.

Materials to avoid

Reactions with acids.

Reactions with alcohols.

Reactions with alkalies.

Reactions with amines.

Hazardous decomposition products

Carbon monoxide and carbon dioxide.

Hydrogen chloride (HCl)

Sulphurous oxides (SO_x)**Additional information**

No decomposition if stored and applied as directed.

11. Toxicological information**Sensitizing effects**

Sensitization through inhalation possible.

Frequent persistent contact with the skin may cause skin irritation.

12. Ecological information**Further information**

Do not discharge product unmonitored into the environment.

Product is not allowed to be discharged into aquatic environment.

13. Disposal considerations**Advice on disposal**

Remove in accordance with local official regulations.

If recycling is not practicable, dispose of in compliance with local regulations.

Contaminated packaging

Empty containers should be taken for local recycling, recovery or waste disposal.

Contaminated packagings are to be treated like the product itself.

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

14. Transport information**Canadian TDG****Proper shipping name**

Not regulated.

Land transport (ADR/RID)

Weicon GmbH

Revision date: 15.12.2009

Revision no.:

1,00

Flex 310, Adhesive and Sealant, different colours

7619-0101

Description of the goods

No hazardous material as defined by the transport regulations.

Other applicable information

No hazardous material as defined by the transport regulations.

15. Regulatory information

Canadian regulations

DSL/NDSL inventory status

All of the components are listed on the DSL Inventory.

National Pollutant Release Inventory (NPRI)

m-Xylene (CAS 108-38-3) (max. 5%)

WHMIS classification

WHMIS: D2A & D2B

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all information required by the CPR.

16. Other information

Other data

Data of sections 4 to 8, as well as 10 to 12, do not necessarily refer to the use and the regular handling of the product (in this sense consult package leaflet and expert information), but to release of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product (s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

"(n.a. = not applicable; n.d. = not determined)"

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)