

Weicon GmbH

Revision date: 26.10.2009

Revision no.:

1,00

Plastic-Metal UW resin

7619-0024

**1. Identification of the substance/preparation and of the company/undertaking****Identification of the substance or preparation**

Plastic-Metal UW resin

**Further trade names**

10440-1

**Use of the substance/preparation**

Adhesive

**Company/undertaking identification****Manufacturer**

Weicon GmbH

Königsberger Straße 255

D-48157 Münster

Telephone: +49 (0) 251 9322 - 0

Telefax: +49 (0) 251 9322 - 244

e-mail: info@weicon.de

Internet: www.weicon.de

Responsible for the safety data sheet: sds@gbk-ingelheim.de

**Supplier**

WEICON Inc.

20 Steckle Place, Unit 20

Kitchener, Ontario N2E 2C3

Telephone: 519 896 5252

Telefax: 519 896 5254

e-mail: info@weicon.ca

Emergency telephone number: 0 11 49 178 433 74 34 (CONSULTANK Lutz Harder GmbH)

**2. Hazards identification****Classification**

Indications of danger : Irritant, Dangerous for the environment

R-phrases:

Irritating to eyes and skin.

May cause sensitization by skin contact.

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**3. Composition/information on ingredients****Chemical characterization ( Mixture )**

Resin for a two-component epoxy adhesive.

**Hazardous components**

CAS-No.	Chemical name	Quantity
25068-38-6	Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)	30-50 %
16096-31-4	1,6-bis(2,3-epoxypropoxy)hexane	1 - 10 %
28064-14-4	Reaktionsprodukt: Bisphenol-F-Epichlorhydrinharze mit durchschnittlichem Molekulargewicht <= 700	1 - 10 %

**4. First aid measures****General information**

Remove contaminated soaked clothing immediately.

In the event of persistent symptoms receive medical treatment.

---

**After inhalation**

Move to fresh air in case of accidental inhalation of vapours or decomposition products.

In the event of symptoms refer for medical treatment.

**After contact with skin**

Wash off immediately with soap and plenty of water.

Consult a doctor if skin irritation persists.

**After contact with eyes**

In case of contact with eyes rinse thoroughly with plenty of water and seek medical advice.

Seek medical treatment by eye specialist.

**After ingestion**

Do not induce vomiting.

If swallowed by mistake drink plenty of water and seek medical treatment.

---

**5. Fire-fighting measures**

**Suitable extinguishing media**

Foam, carbon dioxide (CO<sub>2</sub>), dry chemical, water-spray.

**Extinguishing media which must not be used for safety reasons**

Full water jet

**Special exposure hazards arising from substance or preparation itself, combustion products, resulting gases**

Fire may produce:

Carbon monoxide (CO)

Carbon dioxide (CO<sub>2</sub>)

**Special protective equipment for fire-fighters**

A self contained breathing apparatus should be worn in fire conditions.

**Additional information**

Cool containers at risk with water spray jet.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

---

**6. Accidental release measures**

**Personal precautions**

Use personal protective clothing.

In case of vapour formation use respirator.

Ensure adequate ventilation.

**Environmental precautions**

Clean contaminated surface thoroughly.

Do not discharge into the drains/surface waters/groundwater.

Do not discharge into the subsoil/soil.

**Methods for cleaning up/taking up**

Take up with absorbent material.

Shovel into suitable container for disposal.

---

**7. Handling and storage**

**Handling**

**Advice on safe handling**

Keep container tightly closed.

Use only in thoroughly ventilated areas.

Avoid contact with skin, eyes and clothing.

When using, do not eat, drink or smoke.

**Advice on protection against fire and explosion**

Pay attention to general rules of internal fire prevention.

Weicon GmbH

Revision date: 26.10.2009

Revision no.:

1,00

Plastic-Metal UW resin

7619-0024

**Further information on handling**

Open and handle container with care.

**Storage****Requirements for storage rooms and vessels**

Keep container tightly closed in a dry, cool and well-ventilated place.  
Protect against direct sun radiation.

**Advice on storage compatibility**

Incompatible with:  
Oxidizing agents, Amines, Acids and bases.

**Further information on storage conditions**

Keep away from food, drink and animal feeding stuffs.

Storageclass (VCI): 13

**8. Exposure controls/personal protection****Exposure limit values****Additional advice on limit values**

Contains epoxy compounds. Observe the instructions of the manufacturer

**Occupational exposure controls**

Ensure adequate ventilation, especially in confined areas.

**Protective and hygiene measures**

Do not inhale gases/vapours/aerosols.  
Wash hands before breaks and immediately after handling the product.  
When using, do not eat, drink or smoke.  
Avoid contact with skin, eyes and clothing.  
Remove and wash contaminated clothes before re-use.

**Respiratory protection**

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A).

**Hand protection**

Protective gloves resistant to chemicals made off natural-rubber latex, Minimum coat thickness 0.6 mm,  
Permeation resistance (wear duration) approx. 480 minutes, i.e. protective glove <Lapren 706> made by  
www.kcl.de.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374  
carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the  
recommendations given by the manufacturer of protective gloves.

**Eye protection**

Tightly fitting goggles

**Skin protection**

Light protective clothing  
Safety Shoes

**9. Physical and chemical properties****General information**

Physical state: Pasty  
Colour: Black  
Odour: Perceptible

**Important health, safety and environmental information**

Test method

**Changes in the physical state**

Weicon GmbH

Revision date: 26.10.2009

Revision no.:

1,00

Plastic-Metal UW resin

7619-0024

---

Flash point:	>100 °C
Density (at 20 °C):	1,7 g/cm <sup>3</sup>
Water solubility: (at 20 °C)	Insoluble

---

## 10. Stability and reactivity

### Conditions to avoid

To avoid thermal decomposition, do not overheat.

Keep away from heat.

### Materials to avoid

Reactions with strong acids and alkalis.

Reactions with strong oxidizing agents.

### Hazardous decomposition products

Carbon monoxide and carbon dioxide.

Nitrous oxides (NO<sub>x</sub>)

### Additional information

No decomposition if stored and applied as directed.

---

## 11. Toxicological information

### Corrosive and irritant effects

Skin irritation : Irritant      Rabbit

Eye irritation : Irritant      Rabbit eye

### Sensitizing effects

Sensitization through skin contact possible.

Sensitization skin (guinea pig): Sensitizing

### Empirical data on effects on humans

If appropriately handled and if in accordance with the general hygienic rules, no damages to health have become known.

---

## 12. Ecological information

### Further information

Do not discharge product unmonitored into the environment.

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

---

## 13. Disposal considerations

### Advice on disposal

Remove in accordance with local official regulations.

Where possible recycling is preferred to disposal.

If recycling is not practicable, dispose of in compliance with local regulations.

Empty containers may be recycled. Otherwise dispose of in accordance with applicable regulations.

### Contaminated packaging

Empty containers should be taken for local recycling, recovery or waste disposal.

Contaminated packagings are to be treated like the product itself.

Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.

---

## 14. Transport information

### Canadian TDG

#### Proper shipping name

Environmentally hazardous substance, solid, n.o.s. (Bisphenol A Epoxy Resin )

UN/ID number: UN3077

Hazard classes: 9

Packing group: III

---

Weicon GmbH

Revision date: 26.10.2009

Revision no.:

1,00

Plastic-Metal UW resin

7619-0024

Hazard label: 9

**Land transport (ADR/RID)**

UN number: 3077

ADR/RID class: 9

Classification Code: M7

Warning plate

Hazard-no.: 90

Hazard label: 9



ADR/RID packing group: III

Limited quantity: LQ27

**Description of the goods**

Environmentally hazardous substance, solid, n.o.s. (Bisphenol A Epoxy Resin )

**Other applicable information (land transport)**

Transport category:: 3

Tunnel restriction code:: E

Additional label with symbol "fish and tree" according to subsection 5.2.1.8.3. ADR for single packagings and inner packagings with &gt; 5 kg or 5 L.

**Marine transport**

UN number: 3077

IMDG code: 9

IMDG packing group: III

**Description of the goods**

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (cont. epoxy resin)

**Other applicable information (marine transport)**

Additional label with symbol "fish and tree" according to subsection 5.2.1. IMDG Code for single packagings and inner packagings with &gt; 5 kg or 5 L.

**Air transport**

UN/ID number: 3077

ICAO/IATA-DGR: 9

Hazard label: 9



ICAO packing group: III

IATA-packing instructions - Passenger: 911

IATA-packing instructions - Cargo: 911

**Description of the goods**

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (cont. epoxy resin)

**Other applicable information (air transport)**

Additional label with symbol "fish and tree" according to subsection 7.1.6.3. IATA/DGR for single packagings and inner packagings with &gt; 5 kg or 5 L.

**15. Regulatory information****Canadian regulations****DSL/NDSL inventory status**

All of the components are listed on the DSL Inventory.



Weicon GmbH

Revision date: 26.10.2009

Revision no.:

1,00

Plastic-Metal UW resin

7619-0024

---

**WHMIS classification**

WHMIS: D2B

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all information required by the CPR.

**16. Other information**

**Other data**

Data of sections 4 to 8, as well as 10 to 12, do not necessarily refer to the use and the regular handling of the product (in this sense consult package leaflet and expert information), but to release of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product (s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

"(n.a. = not applicable; n.d. = not determined)"

---

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*