

Weicon GmbH

Revision date: 07.01.2010

Revision no.:

1,00

Rust Loosener liquid

7619-0119

1. Identification of the substance/preparation and of the company/undertaking

Identification of the substance or preparation

Rust Loosener liquid

Further trade names

15150-2

Use of the substance/preparation

Lubricant

Company/undertaking identification

Manufacturer

Weicon GmbH

Königsberger Straße 255

D-48157 Münster

Telephone: +49 (0) 251 9322 - 0

Telefax: +49 (0) 251 9322 - 244

e-mail: info@weicon.de

Internet: www.weicon.de

Responsible for the safety data sheet: sds@gbk-ingelheim.de

Supplier

WEICON Inc.

20 Steckle Place, Unit 20

Kitchener, Ontario N2E 2C3

Telephone: 519 896 5252

Telefax: 519 896 5254

e-mail: info@weicon.ca

Emergency telephone number: 0 11 49 178 433 74 34 (CONSULTANK Lutz Harder GmbH)

2. Hazards identification

Classification

Not classified as dangerous according to directive 1999/45/EEC

3. Composition/information on ingredients

Chemical characterization (Mixture)

Non-hazardous preparation.

Mixture of oils and corrosion protection additives.

Further Information

Although this product does not require a hazard warning label, we recommend that the safety advice should be observed.

4. First aid measures

General information

Remove contaminated soaked clothing immediately.

After inhalation

Move to fresh air in case of accidental inhalation of fumes from overheating or combustion.

In the event of symptoms refer for medical treatment.

After contact with skin

In case of contact with skin wash off with water.

Consult a doctor if skin irritation persists.

After contact with eyes

In case of contact with eyes rinse thoroughly with water.

If eye irritation persists, consult a specialist.

Weicon GmbH

Revision date: 07.01.2010

Revision no.:

1,00

Rust Loosener liquid

7619-0119

After ingestion

Seek medical advice immediately.

5. Fire-fighting measures

Suitable extinguishing media

Foam

Dry powder

Carbon dioxide

Extinguishing media which must not be used for safety reasons

Full water jet

Special exposure hazards arising from substance or preparation itself, combustion products, resulting gases

Fire may produce:

Carbon monoxide and carbon dioxide.

Special protective equipment for fire-fighters

Use breathing apparatus with independent air supply.

Additional information

Collect contaminated firefighting water separately, must not be discharged into the drains.

6. Accidental release measures

Personal precautions

Avoid contact with skin, eyes and clothing.

Ensure adequate ventilation.

Environmental precautions

Do not discharge into the drains or bodies of water.

Do not discharge into the subsoil/soil.

Methods for cleaning up/taking up

Take up with absorbent material.

Shovel into suitable container for disposal.

7. Handling and storage

Handling

Advice on safe handling

Ensure adequate ventilation.

Avoid contact with skin, eyes and clothing.

Advice on protection against fire and explosion

No special measures required.

Keep away from sources of ignition - No smoking.

Storage

Requirements for storage rooms and vessels

Keep containers tightly closed in a cool, well-ventilated place.

Recommended storage temperature: room temperature.

8. Exposure controls/personal protection

Exposure limit values

Occupational exposure controls

Ensure adequate ventilation, especially in confined areas.

Protective and hygiene measures

Avoid contact with eyes and skin.

Wash hands before breaks and immediately after handling the product.

Weicon GmbH

Revision date: 07.01.2010

Revision no.:

1,00

Rust Loosener liquid

7619-0119

At work do not eat, drink, smoke or take drugs.
Remove and wash contaminated clothes before re-use.
Do not inhale aerosols

Respiratory protection

Not required under normal use.
Breathing apparatus in the event of aerosol or mist formation.

Hand protection

Protective gloves resistant to chemicals made of nitrile, Minimum coat thickness 0.4 mm, Permeation resistance (wear duration) approx. 480 minutes, i.e. protective glove <Camatril 735> made by www.kcl.de.

Eye protection

Safety goggles

Skin protection

Protective clothing

9. Physical and chemical properties**General information**

Physical state: Liquid
Colour: Dark yellow
Odour: Oil-like

Important health, safety and environmental information

Test method

Changes in the physical state

Melting point:	<-10 °C
Boiling point:	>170 °C
Flash point:	80 °C
Lower explosion limits:	0,6 vol. %
Upper explosion limits:	8 vol. %
Vapour pressure: (at 20 °C)	<8 hPa
Density (at 20 °C):	0,84 g/cm ³ DIN 51757
Water solubility: (at 20 °C)	Insoluble

Solvent content

96%

Other information

Ignition temperature: >250 °C

10. Stability and reactivity**Materials to avoid**

Keep away from heat and sources of ignition.

Hazardous decomposition products

Carbon monoxide and carbon dioxide.

Additional information

No decomposition if stored and applied as directed.

11. Toxicological information**Acute toxicity**

LD50/oral : >2000 mg/kg Rat (Calculated)

Corrosive and irritant effects

Eye irritation = Low irritant - no labeling duty

Weicon GmbH

Revision date: 07.01.2010

Revision no.:

1,00

Rust Loosener liquid

7619-0119

Has a degreasing effect on the skin.

Empirical data on effects on humans

If appropriately handled and if in accordance with the general hygienic rules, no damages to health have become known.

12. Ecological information**Ecotoxicity**

Ecological data are not available.

Further information

Do not discharge product unmonitored into the environment.

Product is not allowed to discharge into aquatic environment, drains or sewage treatment plants.

13. Disposal considerations**Advice on disposal**

Remove in accordance with local official regulations.

Where possible recycling is preferred to disposal.

If recycling is not practicable, dispose of in compliance with local regulations.

Contaminated packaging

Empty containers should be taken for local recycling, recovery or waste disposal.

14. Transport information**Canadian TDG****Proper shipping name**

Not regulated.

Land transport (ADR/RID)**Description of the goods**

No hazardous material as defined by the transport regulations.

Other applicable information

No hazardous material as defined by the transport regulations.

15. Regulatory information**Canadian regulations****DSL/NDSL inventory status**

All of the components are listed on the DSL Inventory.

WHMIS classification

WHMIS: B3 Combustible.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all information required by the CPR.

16. Other information**Other data**

Data of sections 4 to 8, as well as 10 to 12, do not necessarily refer to the use and the regular handling of the product (in this sense consult package leaflet and expert information), but to release of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product (s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

"(n.a. = not applicable; n.d. = not determined)"

Safety Data Sheet according to WHMIS



Weicon GmbH

Revision date: 07.01.2010

Revision no.:

1,00

Rust Loosener liquid

7619-0119

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)