



1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Name of product	Adhesive Spray "strong" (GB) Code-Nr. 11800
Manufacturer/distributor	WEICON GmbH & Co. KG Königsberger Straße 255, DE-48157 Münster Postbox 84 60, DE-48045 Münster Phone ++49(0)251 / 9322 - 0, Fax ++49(0)251 / 9322-244 E-Mail : info@weicon.de Internet : www.weicon.de
Advice	Abteilung Angebote, Verkauf, Export Phone ++49(0)251 / 9322 - 0
Emergency advice	Giftnotruf Bonn: Bei Vergiftungen (in case of poisoning) Phone ++49(0)228-19 240
Recommended intended purpose(s)	Technical Aerosols

2. HAZARDS IDENTIFICATION

Classification

F+; R12
Xi; R38
N; R51/53

R-phrases

12 Extremely flammable.
38 Irritating to skin.
51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
67 Vapours may cause drowsiness and dizziness.

Special hazards information for humans and environment

In extensive use, formation of flammable / explosive vapour-air mixture is possible.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical characterization

Mixture of active ingredients with propellant

Hazardous ingredients

CAS No	EC No	Name	[% weight]	Classification
92045-53-9	295-434-2	Naphtha (petroleum), hydrodesulfurized light, dearomatized; Low boiling point naphtha - unspecified	25 - 35	F R1;1 Xi R 36; Xn R 65; R 67; N R51/53
115-10-6	204-065-8	dimethylether	35 - 90	F+ R12
64742-49-0	265-151-9	Naphtha (Erdöl), mit Wasserstoff behandelte leichte ; Naphtha, wasserstoffbehandelt, niedrig siedend (Nota P)	1 - 10	F11; Xn R 65; Xi R38; R67; N R51/53



4. FIRST AID MEASURES

General information

Remove contaminated soaked clothing immediately.

In case of inhalation

Ensure of fresh air.

In case of skin contact

In case of contact with skin wash off with water.
Consult a doctor if skin irritation persists.

In case of eye contact

In case of contact with eyes rinse thoroughly with plenty of water and seek medical advice.

In case of ingestion

Do not induce vomiting.
Medical treatment.

Physician's information / possible symptoms

The following symptoms may occur:
Headache
Confusion

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Foam
Dry powder
Carbon dioxide

Extinguishing media which must not be used for safety reasons

Full water jet

Special exposure hazards arising from the substance or preparation itself, combustion products, resulting gases

Danger of bursting
Fire gas of organic material has to be classed invariably as respiratory poison.

Special protective equipment for fire-fighters

Use breathing apparatus with independent air supply.
Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

Additional information

Cool endangered containers with water spray jet.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions

Ensure adequate ventilation.
Use personal protective clothing.
Keep away sources of ignition.

Environmental precautions

Do not discharge into the drains or bodies of water..
Do not discharge into the subsoil/soil.

Methods for cleaning up

Take up with absorbent material.
After taking up the material dispose according to regulation.



7. HANDLING AND STORAGE

Advice on safe handling

Ventilate closed rooms at ground level.

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking

Do not spray on a naked flame or any incandescent material.

Pressurized container.

Do not pierce or burn even after use.

The product is combustible.

Vapours can form an explosive mixture with air.

Avoid effect of heat.

Requirements for storage rooms and vessels

Keep in closed original container.

Adhere to administrative regulations relating to storage of compressed gas cylinders / containers.

Further information on storage conditions

Protect from heat and direct solar radiation.

Keep container in a well-ventilated place

Storage temperature may not exceed 50°C (=122°F).

Store container at cool and aired place.

Recommended storage temperature: room temperature.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with occupational exposure limits to be monitored

CAS No	Name	Code	[mg/m ³]	[ppm]	Spitzenb.	Remark
115-10-6	Dimethyl ether	8 hours	766	400		EH40/2005
		Short-term	958	500		

Indicative occupational exposure limit values (91/322/EEC, 2000/39/EC or 2006/15/EC)

CAS No	Name	Code	[mg/m ³]	[ppm]	Remark
115-10-6	dimethylether	8 hours	1920	1000	

Respiratory protection

Breathing apparatus in the event of aerosol or mist formation.

Short-term: filter apparatus, filter AX, otherwise environment-independent breathing apparatus.

Hand protection

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

Chemical protective gloves must be chosen carefully in view of their design and depending on the dependence on the concentration and amounts of dangerous goods used in the specific working tasks.

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]: fluorinated rubber; 0,7mm; 480min; 60min;

Eye protection

safety goggles

Skin protection

protective clothing

General protective measures

Avoid contact with eyes and skin

Do not inhale gases/vapours/aerosols.

Hygiene measures

At work do not eat, drink, smoke or take drugs.



12. ECOLOGICAL INFORMATION

General regulation

Do not allow uncontrolled leakage of product into the environment.
Product is not allowed to be discharged into aquatic environment.

13. DISPOSAL CONSIDERATIONS

Waste code No.

15 01 10*

16 05 04*

Name of waste

packaging containing residues of or contaminated by dangerous substances

gases in pressure containers (including halons) containing dangerous substances

Wastes marked with an asterisk are considered to be hazardous waste pursuant to Directive 91/689/EEC on hazardous waste.

Recommendations for the product

Remove in accordance with local official regulations.

There are no harmonised regulations on the disposal of chemicals in the member states of the EU. In Germany, the Recycling and Waste Management Act 8 KrW-/AbfG) stipulates recycling as a requirement.

Recommendations for packaging

Dispose of according to the local waste regulations.

Recommended cleansing agent

E.g white spirit.

General information

For proper waste disposal a complete emptying of the tin is necessary.

14. TRANSPORT INFORMATION

Land and inland navigation transport ADR/RID

UN 1950 AEROSOLS, 2.1, (D), Classification code: 5F
transport in "limited quantities" according to 3.4 ADR LQ2 is possible

Marine transport IMDG

UN 1950 AEROSOLS, 2.1

Air transport ICAO/IATA-DGR

UN 1950 Aerosols, flammable, 2.1

Transport/further information

24h EMERGENCY CONTACT (TRANSPORT) +49(0)178 433 7434 (Consultank GmbH)

15. REGULATORY INFORMATION

Remarks for classification

The product is classified and labelled in accordance with EC directives.

Classification

- F+** Extremely flammable
- Xi** Irritant
- N** Dangerous for the environment

R-phrases

- 12 Extremely flammable.
- 38 Irritating to skin.
- 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- 67 Vapours may cause drowsiness and dizziness.

S-phrases

- 23.4 Do not breathe spray.



Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

Printed 29.09.2009

Revision 20.09.2009 (GB) Version 5.5

Adhesive Spray "strong" (GB)

- 37 Wear suitable gloves.
51 Use only in well-ventilated areas.
61 Avoid release to the environment. Refer to special instructions/safety data sheets.

Hazardous ingredients for labeling

Naphtha (Erdöl), mit Wasserstoff behandelte leichte aromatenfrei

Special labelling for certain preparations

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material.

Without sufficient ventilation the formation of explosive vapour/air mixtures cannot be excluded. Keep away from sources of ignition - No smoking. Keep out of the reach of children.

VOC standard

VOC content 59,7 %

VOC value 597 g/L

16. OTHER INFORMATION

Recommend uses and restrictions

National and local regulations concerning chemicals shall be observed.

Further information

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Wording of the R-phrases specified in chapter 3 (not the classification of the formulation!)

- R 11 Highly flammable.
R 12 Extremely flammable.
R 36 Irritating to eyes.
R 38 Irritating to skin.
R 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R 65 Harmful: may cause lung damage if swallowed.
R 67 Vapours may cause drowsiness and dizziness.