



1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Name of product	Anti-Seize "High-Tech" Assembly Spray (GB) Code-Nr. 27050
Manufacturer/distributor	WEICON GmbH & Co. KG Königsberger Straße 255, DE-48157 Münster Postbox 84 60, DE-48045 Münster Phone ++49(0)251 / 9322 - 0, Fax ++49(0)251 / 9322-244 E-Mail : info@weicon.de Internet : www.weicon.de
Advice	Abteilung Angebote, Verkauf, Export Phone ++49(0)251 / 9322 - 0
Emergency advice	Giftnotruf Bonn: Bei Vergiftungen (in case of poisoning) Phone ++49(0)228-19 240
Recommended intended purpose(s)	Corrosion Protection and Lubricant

2. HAZARDS IDENTIFICATION

Classification

F+; R12
R52/53

R-phrases

12 Extremely flammable.
52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
67 Vapours may cause drowsiness and dizziness.

Special hazards information for humans and environment

In extensive use, formation of flammable / explosive vapour-air mixture is possible.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical characterization

Lubrication spray based on solvents. Propellant: propane / butane.

Hazardous ingredients

CAS No	EC No	Name	[% weight]	Classification
67-63-0	200-661-7	propan-2-ol	< 2	F R11; Xi R36; R67
64742-49-0	265-151-9	Naphtha (Erdöl), mit Wasserstoff behandelte leichte ; Naphtha, wasserstoffbehandelt, niedrig siedend (Nota P)	15 - 19	F R11; Xn R65; Xi R38; N R51/53; R67
1305-62-0	215-137-3	calcium hydroxide	< 2	Xi, R38-41
61641-74-5		propane/butane-mixture	40-50	F+, R12



4. FIRST AID MEASURES

General information

Remove moisted clothing immediately.

In case of inhalation

Remove the casualty into fresh air and keep him immobile.
In the event of symptoms refer for medical treatment.

In case of skin contact

In case of contact with skin wash off with soap and water.

In case of eye contact

In case of contact with eyes rinse thoroughly with plenty of water and seek medical advice.

In case of ingestion

Do not induce vomiting.
Medical treatment.

Physician's information / possible symptoms

The following symptoms may occur:
Unconsciousness
Anaesthetic state
Headache
Confusion
Dizziness

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Foam
Dry powder
Carbon dioxide

Extinguishing media which must not be used for safety reasons

Full water jet

Special exposure hazards arising from the substance or preparation itself, combustion products, resulting gases

Fire gas of organic material has to be classed invariably as respiratory poison.

Special protective equipment for fire-fighters

Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.
Do not inhale explosion and/or combustion gases.

Additional information

Cool endangered containers with water spray jet.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions

High risk of slipping due to leakage/spillage of product.

Environmental precautions

Do not discharge into the drains or bodies of water..

Methods for cleaning up

Take up with absorbent material (e.g. sand, kieselguhr, acid binder, general-purpose binder, sawdust).
After taking up the material dispose according to regulation.

Additional Information

Sort out leaky cans and dispose according to regulations.



7. HANDLING AND STORAGE

Advice on safe handling

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.
Provide good room ventilation even at ground level (vapours are heavier than air).

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking
Do not spray on a naked flame or any incandescent material.
Do not pierce or burn even after use.
The product is combustible.
Vapours can form an explosive mixture with air.
Avoid effect of heat.

Requirements for storage rooms and vessels

Keep in closed original container.
Adhere to administrative regulations relating to storage of compressed gas cylinders / containers.

Advice on storage compatibility

Do not store with combustible materials.

Further information on storage conditions

Protect from heat and direct solar radiation.
Storage temperature may not exceed 50°C (=122°F).
Store container at cool and aired place.
Keep in a cool place.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with occupational exposure limits to be monitored

CAS No	Name	Code	[mg/m ³]	[ppm]	Spitzenb.	Remark
106-97-8	Butane	8 hours	1450	600		EH40/2005
		Short-term	1810	750		
1305-62-0	Calcium hydroxide	8 hours	5			EH40/2005
67-63-0	propan-2-ol	8 hours	999	400		EH40/2005
		Short-term	1250	500		

Respiratory protection

If ventilation insufficient, wear respiratory protection.
Breathing apparatus

Hand protection

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]:: Nitrile rubber; 0,4mm; 480min;60min.

Eye protection

safety goggles

Skin protection

protective clothing

General protective measures

Do not inhale gases.
Do not inhale aerosols

Hygiene measures

At work do not eat, drink and smoke.
Wash hands before breaks and after work.



12. ECOLOGICAL INFORMATION

General regulation

Do not allow uncontrolled leakage of product into the environment.
Product is not allowed to be discharged into aquatic environment.

13. DISPOSAL CONSIDERATIONS

Waste code No.

15 01 10*

Name of waste

packaging containing residues of or contaminated by dangerous substances

Wastes marked with an asterisk are considered to be hazardous waste pursuant to Directive 91/689/EEC on hazardous waste.

Recommendations for the product

Remove in accordance with local official regulations.

Recommendations for packaging

Dispose of according to the local waste regulations.

General information

For proper waste disposal a complete emptying of the tin is necessary.

14. TRANSPORT INFORMATION

Land and inland navigation transport ADR/RID

UN 1950 AEROSOLS, 2.1, (D), Classification code: 5F
transport in "limited quantities" according to 3.4 ADR LQ2 is possible

Marine transport IMDG

UN 1950 AEROSOLS, 2.1

Air transport ICAO/IATA-DGR

UN 1950 Aerosols, flammable, 2.1

Transport/further information

24h EMERGENCY CONTACT (TRANSPORT) +49(0)178 433 7434 (Consultank GmbH)

15. REGULATORY INFORMATION

Remarks for classification

The product is classified and labelled in accordance with EC directives/German regulations on dangerous substances.

Classification

F+ Extremely flammable

R-phrases

12 Extremely flammable.
52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
67 Vapours may cause drowsiness and dizziness.

S-phrases

23.4 Do not breathe spray.
51 Use only in well-ventilated areas.

Special labelling for certain preparations

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material.

Without sufficient ventilation the formation of explosive vapour/air mixtures cannot be excluded. Keep away from sources of ignition - No smoking. Keep out of the reach of children.



VOC standard
VOC value 0,194 g/L

16. OTHER INFORMATION

Recommend uses and restrictions

National and local regulations concerning chemicals shall be observed.

Further information

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Wording of the R-phrases specified in chapter 3 (not the classification of the formulation!)

- R 11 Highly flammable.
- R 12 Extremely flammable.
- R 36 Irritating to eyes.
- R 38 Irritating to skin.
- R 41 Risk of serious damage to eyes.
- R 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- R 65 Harmful: may cause lung damage if swallowed.
- R 67 Vapours may cause drowsiness and dizziness.