



## 1. Identification of the substance/mixture and of the company/undertaking

### Product identifier

**Name of product** Cleaner S, liquid (GB)  
Code-Nr. 152000

### Manufacturer/distributor

WEICON GmbH & Co. KG  
Königsberger Straße 255, DE-48157 Münster  
Postbox 84 60, DE-48045 Münster  
Phone ++49(0)251 / 9322 - 0, Fax ++49(0)251 / 9322-244  
E-Mail : info@weicon.de  
Internet : www.weicon.de

### Advice

Abteilung Angebote, Verkauf, Export  
Phone ++49(0)251 / 9322 - 0

### Emergency advice

Giftnotruf Bonn: Bei Vergiftungen (in case of poisoning)  
Phone ++49(0)228-19 240

### Recommended intended purpose(s)

Technical Liquids

## 2. Hazards identification

### Classification according to 67/548/EEC or 1999/45/EC

F; R11  
Xi; R36/38  
N; R51/53  
Xn; R65  
R67

### R-phrases

11 Highly flammable.  
36/38 Irritating to eyes and skin.  
51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
65 Harmful: may cause lung damage if swallowed.  
67 Vapours may cause drowsiness and dizziness.

### Labelling according to 67/548/EEC or 1999/45/EC

#### Remarks for labelling

The product is classified and labelled in accordance with EC directives/German regulations on dangerous substances.

**F** Highly flammable  
**Xn** Harmful  
**N** Dangerous for the environment

### R-phrases

11 Highly flammable.  
36/38 Irritating to eyes and skin.  
51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
65 Harmful: may cause lung damage if swallowed.  
67 Vapours may cause drowsiness and dizziness.



#### S-phrases

- 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
61 Avoid release to the environment. Refer to special instructions/safety data sheets.  
62 If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

#### Information pertaining to special dangers for human and environment

In extensive use, formation of flammable / explosive vapour-air mixture is possible.

### 3. Composition/information on ingredients

#### Hazardous ingredients

CAS No	EC No	Name	[% weight]	Classification according to 67/548/EEC
67-63-0	200-661-7	propan-2-ol	20 - 30	F R11; Xi R36; R67
67-64-1	200-662-2	acetone	10 - 20	F R11; Xi R36; R66; R67
64742-49-0	265-151-9	Aliphatic hydrocarbon (note H,P)	1 - 10	F R11; Xn R65; Xi R38; N R51/53; R67
64742-49-0	265-151-9	Naphtha (petroleum) hydrotreated light; naphtha hydrotreated, low-boiling (note P)	30 - 50	F11; Xn R 65; Xi R38; R67; N R51/53

### 4. First aid measures

#### General information

Remove contaminated soaked clothing immediately.

#### In case of inhalation

Ensure of fresh air.

In the event of symptoms refer for medical treatment.

#### In case of skin contact

In case of contact with skin wash off with soap and water.

#### In case of eye contact

In case of contact with eyes rinse thoroughly with plenty of water and seek medical advice.

#### In case of ingestion

If swallowed or in case of vomiting, danger of infiltration into the lungs (danger of aspiration).

Do not induce vomiting.

Medical treatment.

#### Physician's information / possible symptoms

The following symptoms may occur:

Unconsciousness

Delirious state

vomiting

Headache

Confusion

### 5. Firefighting measures

#### Suitable extinguishing media

Alcohol-resistant foam

Dry powder

Carbon dioxide

#### Extinguishing media which must not be used for safety reasons

Full water jet

#### Special hazards arising from the substance or mixture

Fire gas of organic material has to be classed invariably as respiratory poison.



**Special protective equipment for fire-fighters**

Use breathing apparatus with independent air supply.

Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

**Additional information**

Cool endangered containers with water spray jet.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

**6. Accidental release measures**

**Personal precautions**

Ensure adequate ventilation.

Use personal protective clothing.

Keep away sources of ignition.

**Environmental precautions**

Do not discharge into the drains or bodies of water..

**Methods for cleaning up**

Disposal according to regulations.

Take up with absorbent material.

**7. Handling and storage**

**Advice on safe handling**

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

**Advice on protection against fire and explosion**

Keep away from sources of ignition - No smoking

Do not pierce or burn even after use.

The product is combustible.

Vapours can form an explosive mixture with air.

Avoid effect of heat.

**Requirements for storage rooms and vessels**

Only use containers that are approved specifically for the substance/product.

**Further information on storage conditions**

Protect from heat and direct solar radiation.

Keep container in a well-ventilated place

Keep in a cool place.

**8. Exposure controls/personal protection**

**Additional advice on system design**

Sufficient ventilation and exhaustion.

**Ingredients with occupational exposure limits to be monitored**

CAS No	Name	Code	[mg/m3]	[ppm]	Remark
67-64-1	Acetone	8 hours	1210	500	EH40/2005
		Short-term	3620	1500	
67-63-0	propan-2-ol	8 hours	999	400	EH40/2005
		Short-term	1250	500	



# Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

Printed 11.02.2011

Revision 10.02.2011 (GB) Version 6.0

## Cleaner S, liquid (GB)

### Indicative occupational exposure limit values (91/322/EEC, 2000/39/EC, 2006/15/EC or 2009/161/EU)

CAS No	Name	Code	[mg/m <sup>3</sup> ]	[ppm]	Remark
67-64-1	acetone	8 hours	1210	500	

#### Respiratory protection

Environment-independent breathing apparatus.

If ventilation insufficient, wear respiratory protection.

Multi-purpose filter ABEK/P3

#### Hand protection

Die einzusetzenden Schutzhandschuhe müssen den Spezifikationen der EG-Richtlinie 89/686/EWG und der sich daraus ergebenden Norm EN374 genügen.

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]: Nitrile rubber; 0,4mm; 480min;60min.

Chemical protective gloves must be chosen carefully in view of their design and depending on the dependence on the concentration and amounts of dangerous goods used in the specific working tasks.

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]: butyl rubber, 0,7mm; 480min

#### Eye protection

safety goggles with side protection

#### Skin protection

protective clothing

#### General protective measures

Avoid contact with eyes and skin

Do not inhale gases/vapours/aerosols.

#### Hygiene measures

Cloths contaminated with product should not be kept in trouser pockets.

At work do not eat, drink, smoke or take drugs.

Wash hands before breaks and after work.

## 9. Physical and chemical properties

<b>Form</b>	<b>Colour</b>	<b>Odour</b>
liquid	colourless, clear	pleasant

### Important health, safety and environmental information

	Value	Temperature	at	Method	Remark
<b>boiling range</b>	60 - 110 °C				
<b>melting range</b>	< -30 °C				
<b>Flash point</b>	-20 °C				propellant
<b>Ignition temperature</b>	> 260 °C				propellant
<b>Lower explosion limit</b>	0,8 Vol-%				
<b>Upper explosion limit</b>	13 Vol-%				
<b>Vapour pressure</b>	200 hPa	20 °C			



	Value	Temperature	at	Method	Remark
<b>Density</b>	0,73 g/ml	20 °C			
<b>Solubility in water</b>					difficult to dissolve

**Explosive properties**

The product is considered non-explosive ; nevertheless explosive vapour/air mixtures can be generated .

**10. Stability and reactivity**

**Conditions to avoid**

Keep away from heat.

Uncleaned empty vessels may contain product gases which can form explosive mixtures with air.

**Materials to avoid**

Reactions with oxidising agents.

**Hazardous decomposition products**

Carbon monoxide and carbon dioxide.

**Thermal decomposition**

Remark No decomposition if used as directed.

**11. Toxicological information**

**Experiences made from practice**

Often and long skin contact may cause degreasing and desiccation of the skin which may caus skin irritation.

Risk of strong health injuries in case of long-term exposition.

Inhalation can cause damage to the respiratory tract or lungs.

Irritates respiratory tract.

Inhalation causes narcotic effect/intoxication.

**Additional information**

The product is to be handled with the caution usual with chemicals.

The product was classified on the basis of the calculation procedure of the preparation directive (1999/45/EC).

**12. Ecological information**

**Data on elimination (persistence and degradability)**

	Elimination rate	Method of analysis	Method	Validation
<b>Physico-chemical degradability</b>	The product is highly volatile and can be largely eliminated from the water by stripping.			
<b>Biological degradability</b>	The product is slightly degradable.			

**Additional ecological information**

	Value	Method	Remark
<b>AOX</b>	The product contains no organically bound halogen in accordance with the formulation.		

**General regulation**

Because of damage to water organism do not fill in presurge.

Do not allow uncontrolled leakage of product into the environment.



Product is not allowed to be discharged into aquatic environment.

### 13. Disposal considerations

Waste code No.	Name of waste
15 01 04	metallic packaging
15 01 10*	packaging containing residues of or contaminated by dangerous substances

Wastes marked with an asterisk are considered to be hazardous waste pursuant to Directive 91/689/EEC on hazardous waste.

#### Recommendations for the product

Remove in accordance with local official regulations.

There are no harmonised regulations on the disposal of chemicals in the member states of the EU. In Germany, the Recycling and Waste Management Act 8 KrW-/AbfG) stipulates recycling as a requirement.

This means that a distinction must be made between "wastes for recycling" and "wastes for disposal". Particular aspects - in the main concerning delivery - are also governed by the Laender.

#### Recommendations for packaging

Dispose of according to the local waste regulations.

### 14. Transport information

#### Land and inland navigation transport ADR/RID

UN 1993 FLAMMABLE LIQUID, N.O.S. (Propan-2-ol, Aceton Mischung), 3, II, (D/E), Special provisions 640C, Classification code: F1

transport in "limited quantities" according to 3.4 ADR LQ2 is possible

#### Marine transport IMDG

UN 1993 FLAMMABLE LIQUID, N.O.S. (Propan-2-ol, ACETON Mixture; NAPHTHA (PETROLEUM)), 3, II, MARINE POLLUTANT

#### Air transport ICAO/IATA-DGR

UN 1993 Flammable liquid, n.o.s. (Propan-2-ol, ACETON Mixture), 3, II

#### Transport/further information

24h EMERGENCY CONTACT (TRANSPORT) +49(0)178 433 7434 (Consultank Lutz Harder GmbH)

### 15. Regulatory information

#### VOC standard

VOC content	72,9 %
VOC value	729 g/L

### 16. Other information

#### Recommend uses and restrictions

National and local regulations concerning chemicals shall be observed.

#### Further information

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

#### Wording of the R/H-phrases specified in chapter 3 (not the classification of the mixture!)

R 11 Highly flammable.

R 36 Irritating to eyes.

R 38 Irritating to skin.

R 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R 65 Harmful: may cause lung damage if swallowed.

R 66 Repeated exposure may cause skin dryness or cracking.

R 67 Vapours may cause drowsiness and dizziness.