



1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Name of product	Contact Spray (GB) Code-Nr. 11152
Manufacturer/distributor	WEICON GmbH & Co. KG Königsberger Straße 255, DE-48157 Münster Postbox 84 60, DE-48045 Münster Phone ++49(0)251 / 9322 - 0, Fax ++49(0)251 / 9322-244 E-Mail : info@weicon.de Internet : www.weicon.de
Advice	Abteilung Angebote, Verkauf, Export Phone ++49(0)251 / 9322 - 0
Emergency advice	Giftnotruf Bonn: Bei Vergiftungen (in case of poisoning) Phone ++49(0)228-19 240
Recommended intended purpose(s)	Technical Aerosols

2. HAZARDS IDENTIFICATION

Classification according to 67/548/EEC or 1999/45/EC

F+; R12

Xn; R65

R-phrases

12 Extremely flammable.

66 Repeated exposure may cause skin dryness or cracking.

Information pertaining to special dangers for human and environment

In extensive use, formation of flammable / explosive vapour-air mixture is possible.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous ingredients

CAS No	EC No	Name	[% weight]	Classification according to 67/548/EEC
111-76-2	203-905-0	2-butoxyethanol	<= 2,5	Xn R20/21/22; Xi R36/38
64742-47-8	265-149-8	Distillates (petroleum), hydrotreated light	25 - 50	Xn R65; R66

4. FIRST AID MEASURES

General information

Remove contaminated soaked clothing immediately.

In case of inhalation

Remove the casualty into fresh air and keep him immobile.

In the event of symptoms refer for medical treatment.

In case of skin contact

In case of contact with skin wash off with water.

Consult a doctor if skin irritation persists.



In case of eye contact

In case of contact with eyes rinse thoroughly with plenty of water and seek medical advice.

In case of ingestion

Do not induce vomiting.
Refer to medical treatment.

Physician's information / possible symptoms

The following symptoms may occur:

Unconsciousness
Anaesthetic state
Headache
Confusion

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Alcohol-resistant foam
Dry powder
Carbon dioxide

Extinguishing media which must not be used for safety reasons

water
Full water jet

Special exposure hazards arising from the substance or preparation itself, combustion products, resulting gases

Bildung explosionsfähiger/leichtentzündlicher Dampf-Luftgemische möglich.
Danger of bursting
Fire gas of organic material has to be classed invariably as respiratory poison.

Special protective equipment for fire-fighters

Use breathing apparatus with independent air supply.
Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

Additional information

Cool endangered containers with water spray jet.
Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions

Ensure adequate ventilation.
Use personal protective clothing.
Keep away sources of ignition.

Environmental precautions

Do not discharge into the drains or bodies of water..

Methods for cleaning up

Take up with absorbent material.
After taking up the material dispose according to regulation.

7. HANDLING AND STORAGE

Advice on safe handling

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking
Do not spray on a naked flame or any incandescent material.
Pressurized container.

**Contact Spray (GB)**

Do not pierce or burn even after use.
Vapours can form an explosive mixture with air.
Avoid effect of heat.

Requirements for storage rooms and vessels

Keep in closed original container.
Adhere to administrative regulations relating to storage of compressed gas cylinders / containers.

Further information on storage conditions

Protect from heat and direct solar radiation.
Storage temperature may not exceed 50°C (=122°F).
Store container at cool and aired place.
Recommended storage temperature: room temperature.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Additional advice on system design**

Sufficient ventilation and exhaustion.

Ingredients with occupational exposure limits to be monitored

CAS No	Name	Code	[mg/m3]	[ppm]	Spitzenb.	Remark
106-97-8	Butane	8 hours	1450	600		EH40/2005
		Short-term	1810	750		
111-76-2	2-butoxyethanol	8 hours		25		EH40/2005
		Short-term		50		

Indicative occupational exposure limit values (91/322/EEC, 2000/39/EC or 2006/15/EC)

CAS No	Name	Code	[mg/m3]	[ppm]	Remark
111-76-2	2-butoxyethanol	8 hours	98	20	skin
		Short-term	246	50	

Respiratory protection

In case of insufficient ventilation or long-term effect use breathing apparatus.
Breathing apparatus in the event of aerosol or mist formation.
Short-term: filter apparatus, filter AX, otherwise environment-independent breathing apparatus.

Hand protection

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

Chemical protective gloves must be chosen carefully in view of their design and depending on the dependence on the concentration and amounts of dangerous goods used in the specific working tasks.

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]: fluorinated rubber; 0,7mm; 480min; 60min;

Eye protection

safety goggles

Skin protection

protective clothing

General protective measures

Avoid contact with eyes and skin
Do not inhale aerosols

Hygiene measures

At work do not eat, drink and smoke.



13. DISPOSAL CONSIDERATIONS

Waste code No.	Name of waste
15 01 04	metallic packaging
16 05 04*	gases in pressure containers (including halons) containing dangerous substances

Wastes marked with an asterisk are considered to be hazardous waste pursuant to Directive 91/689/EEC on hazardous waste.

Recommendations for the product

Remove in accordance with local official regulations.

Recommendations for packaging

Dispose of according to the local waste regulations.

General information

For proper waste disposal a complete emptying of the tin is necessary.

14. TRANSPORT INFORMATION

Land and inland navigation transport ADR/RID

UN 1950 AEROSOLS, 2.1, (D), Classification code: 5F
transport in "limited quantities" according to 3.4 ADR LQ2 is possible

Marine transport IMDG

UN 1950 AEROSOLS, 2.1

Air transport ICAO/IATA-DGR

UN 1950 Aerosols, flammable, 2.1

Transport/further information

24h EMERGENCY CONTACT (TRANSPORT) +49(0)178 433 7434 (Consultank Lutz Harder GmbH)

15. REGULATORY INFORMATION

Remarks for labelling

The product is classified and labelled in accordance with EC directives.

Labelling according to 67/548/EEC or 1999/45/EC

F+ Extremely flammable

R-phrases

12 Extremely flammable.
66 Repeated exposure may cause skin dryness or cracking.

S-phrases

23 Do not breathe spray.
46 If swallowed, seek medical advice immediately and show this container or label.
51 Use only in well-ventilated areas.
56 Dispose of this material and its container to hazardous or special waste collection point.

Special labelling for certain preparations

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Without sufficient ventilation the formation of explosive vapour/air mixtures cannot be excluded. Keep away from sources of ignition - No smoking. Keep out of the reach of children.

VOC standard

VOC content	85,71 %
VOC value	599,7 g/L



Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

Printed 09.08.2010

Revision 09.08.2010 (GB) Version 0.0

Contact Spray (GB)

16. OTHER INFORMATION

Recommend uses and restrictions

National and local regulations concerning chemicals shall be observed.

Further information

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Please observe the following disclaimer! --- Our safety data sheets have been compiled according to effective EU-directives, WITHOUT taking into account the special national directives concerning the handling of hazardous substances.

Wording of the R-phrases specified in chapter 3 (not the classification of the formulation!)

R 20/21/22 Harmful by inhalation, in contact with skin and if swallowed.

R 36/38 Irritating to eyes and skin.

R 65 Harmful: may cause lung damage if swallowed.

R 66 Repeated exposure may cause skin dryness or cracking.