



Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

Printed 11.02.2011

Revision 10.02.2011 (GB) Version 6.0

Mould Release Agent liquid (GB)

1. Identification of the substance/mixture and of the company/undertaking

Product identifier

Name of product

Mould Release Agent liquid (GB)
Code-Nr. 154500

Manufacturer/distributor

WEICON GmbH & Co. KG
Königsberger Straße 255, DE-48157 Münster
Postbox 84 60, DE-48045 Münster
Phone ++49(0)251 / 9322 - 0, Fax ++49(0)251 / 9322-244
E-Mail : info@weicon.de
Internet : www.weicon.de

Advice

Abteilung Angebote, Verkauf, Export
Phone ++49(0)251 / 9322 - 0

Emergency advice

Giftnotruf Bonn: Bei Vergiftungen (in case of poisoning)
Phone ++49(0)228-19 240

Recommended intended purpose(s)

Technical Liquids

2. Hazards identification

Classification according to 67/548/EEC or 1999/45/EC

F; R11

Xi; R38

N; R51/53

Xn; R65

R67

R-phrases

11 Highly flammable.

38 Irritating to skin.

51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

65 Harmful: may cause lung damage if swallowed.

67 Vapours may cause drowsiness and dizziness.

Labelling according to 67/548/EEC or 1999/45/EC

Remarks for labelling

The product is classified and labelled in accordance with EC directives/German regulations on dangerous substances.

F Highly flammable

Xn Harmful

N Dangerous for the environment

R-phrases

11 Highly flammable.

38 Irritating to skin.

51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

65 Harmful: may cause lung damage if swallowed.

67 Vapours may cause drowsiness and dizziness.

**Mould Release Agent liquid (GB)****S-phrases**

16	Keep away from sources of ignition - No smoking.
2	Keep out of the reach of children.
23	Do not breathe gas/fumes/vapour/spray.
29	Do not empty into drains.
51	Use only in well-ventilated areas.
62	If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

Hazardous ingredients for labeling

Naphtha (Erdöl), mit Wasserstoff behandelte leichte aromatenfrei

3. Composition/information on ingredients**Description**

Mixture of oil and solvents

Hazardous ingredients

CAS No	EC No	Name	[% weight]	Classification according to 67/548/EEC
64742-49-0	265-151-9	Naphtha (petroleum) hydrotreated light; naphtha hydrotreated, low-boiling (note P)	50 - 100	F R11; Xn R65; Xi R38; N R51/53; R67

4. First aid measures**General information**

Remove contaminated soaked clothing immediately.

In case of inhalation

Remove the casualty into fresh air and keep him immobile.

In the event of symptoms refer for medical treatment.

In case of skin contact

In case of contact with skin wash off with water.

In case of eye contact

In case of contact with eyes rinse thoroughly with plenty of water and seek medical advice.

In case of ingestion

If swallowed or in case of vomiting, danger of infiltration into the lungs (danger of aspiration).

Do not induce vomiting.

Medical treatment.

If swallowed give water to drink.

5. Firefighting measures**Suitable extinguishing media**

Foam

Dry fire-extinguishing substance

Carbon dioxide

Water spray jet

Extinguishing media which must not be used for safety reasons

Full water jet

Special hazards arising from the substance or mixture

Fire gas of organic material has to be classed invariably as respiratory poison.

Special protective equipment for fire-fighters

Use breathing apparatus with independent air supply.



Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

Additional information

Fight fire from protected place.

6. Accidental release measures

Personal precautions

Ensure adequate ventilation.

Keep away sources of ignition.

Environmental precautions

Do not discharge into the drains or bodies of water..

Do not discharge into the subsoil/soil.

Methods for cleaning up

Take up with absorbent material (e.g. sand).

After taking up the material dispose according to regulation.

7. Handling and storage

Advice on safe handling

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking

Vapours can form an explosive mixture with air.

Take precautionary measures against static discharges.

Requirements for storage rooms and vessels

Keep in closed original container.

Further information on storage conditions

Protect from direct solar radiation.

Storage temperature may not exceed 50°C (=122°F).

Store container at cool and aired place.

Store in a dry place.

8. Exposure controls/personal protection

Respiratory protection

If ventilation insufficient, wear respiratory protection.

Hand protection

PVC gloves

Eye protection

safety goggles

Skin protection

Light protective clothing.

General protective measures

Avoid contact with eyes and skin

Do not inhale gases/vapours/aerosols.

Hygiene measures

At work do not eat, drink, smoke or take drugs.

Wash hands before breaks and after work.



13. Disposal considerations

Waste code No.	Name of waste
07 01 04*	other organic solvents, washing liquids and mother liquors
20 01 13*	solvents

Wastes marked with an asterisk are considered to be hazardous waste pursuant to Directive 91/689/EEC on hazardous waste.

Recommendations for the product

Remove in accordance with local official regulations.

Recommendations for packaging

Dispose of according to the local waste regulations.

14. Transport information

Land and inland navigation transport ADR/RID

UN 1268 PETROLEUM DISTILLATES, N.O.S. (NAPHTHA (PETROLEUM)), 3, II, (D/E), Special provisions 640D, Classification code: F1

Marine transport IMDG

UN 1268 PETROLEUM DISTILLATES, N.O.S. (NAPHTHA (PETROLEUM)), 3, II, Marine Pollutant

Air transport ICAO/IATA-DGR

UN 1268 Petroleum distillates, n.o.s. (NAPHTHA (PETROLEUM)), 3, II

Transport/further information

24h EMERGENCY CONTACT (TRANSPORT) +49(0)178 433 7434 (Consultank Lutz Harder GmbH)

15. Regulatory information

VOC standard	
VOC value	624 g/L

16. Other information

Recommend uses and restrictions

National and local regulations concerning chemicals shall be observed.

Further information

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Wording of the R/H-phrases specified in chapter 3 (not the classification of the mixture!)

R 11 Highly flammable.

R 38 Irritating to skin.

R 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R 65 Harmful: may cause lung damage if swallowed.

R 67 Vapours may cause drowsiness and dizziness.