



## 1. Identification of the substance/mixture and of the company/undertaking

### Product identifier

**Name of product** Plastic-Metal SF Resin (GB)  
Code-Nr. 102501

### Manufacturer/distributor

WEICON GmbH & Co. KG  
Königsberger Straße 255, DE-48157 Münster  
Postbox 84 60, DE-48045 Münster  
Phone ++49(0)251 / 9322 - 0, Fax ++49(0)251 / 9322-244  
E-Mail : info@weicon.de  
Internet : www.weicon.de

### Advice

Abteilung Angebote, Verkauf, Export  
Phone ++49(0)251 / 9322 - 0

### Emergency advice

Giftnotruf Bonn: Bei Vergiftungen (in case of poisoning)  
Phone ++49(0)228-19 240

### Recommended intended purpose(s)

2-Component Epoxy Resin - Resin Component

## 2. Hazards identification

### Classification according to 67/548/EEC or 1999/45/EC

Xi; R36/38  
R43  
R52/53

### R-phrases

36/38 Irritating to eyes and skin.  
43 May cause sensitisation by skin contact.  
52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

### Labelling according to 67/548/EEC or 1999/45/EC

### Remarks for labelling

The product is classified and labelled in accordance with EC directives.

**Xi** Irritant

### R-phrases

36/38 Irritating to eyes and skin.  
43 May cause sensitisation by skin contact.  
52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

### S-phrases

2 Keep out of the reach of children.  
28 After contact with skin, wash immediately with plenty of water and soap.  
36/37/39 Wear suitable protective clothing, gloves and eye/face protection.  
46 If swallowed, seek medical advice immediately and show this container or label.  
61 Avoid release to the environment. Refer to special instructions/safety data sheets.

#### Hazardous ingredients for labeling

1,6-bis(2,3-epoxypropoxy)hexane, Bisphenol-A-Epichlorhydrinharze mit durchschnittlichem Molekulargewicht < 700, bisphenol f epoxy resin

#### Special rules for supplemental label elements for certain mixtures

Contains epoxy constituents. See information supplied by the manufacturer.

### 3. Composition/information on ingredients

#### Description

Formulated Bisphenol-A-Epoxy Resin.

#### Hazardous ingredients

CAS No	EC No	Name	[% weight]	Classification according to 67/548/EEC
14807-96-6	238-877-9	talcum (Mg3H2(SiO3)4)	4 - 10	-
16096-31-4	240-260-4	1,6-bis(2,3-epoxypropoxy)hexane	1 - 7	Xi R36/38; R43; R52/53
9003-36-5	500-006-8	bisphenol f epoxy resin	1 - 7	Xi, R36/38, R43, N R51/53
25068-38-6	500-033-5	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)	4 - 10	Xi R36/38; R43; N R51-53

### 4. First aid measures

#### General information

Remove contaminated soaked clothing immediately.

#### In case of inhalation

Ensure of fresh air.

In the event of symptoms refer for medical treatment.

#### In case of skin contact

In case of contact with skin wash off with soap and water.

Consult a doctor if skin irritation persists.

#### In case of eye contact

In case of contact with eyes rinse thoroughly with plenty of water and seek medical advice.

#### In case of ingestion

Do not induce vomiting.

Refer to medical treatment.

If swallowed by mistake drink plenty of water and seek medical treatment.

### 5. Firefighting measures

#### Suitable extinguishing media

Foam

Dry fire-extinguishing substance

Carbon dioxide

Water spray jet

#### Extinguishing media which must not be used for safety reasons

Full water jet

#### Special hazards arising from the substance or mixture

Fire gas of organic material has to be classed invariably as respiratory poison.

In case of fire formation of dangerous gases possible.

Carbon monoxide (CO)

Carbon dioxide (CO2)



**Special protective equipment for fire-fighters**

Use breathing apparatus with independent air supply.

Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

**Additional information**

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

Collect contaminated firefighting water separately, must not be discharged into the drains.

**6. Accidental release measures**

**Personal precautions**

Ensure adequate ventilation.

Use personal protective clothing.

Keep away sources of ignition.

**Environmental precautions**

Do not discharge into the drains/surface waters/groundwater.

Do not discharge into the subsoil/soil.

**Methods for cleaning up**

Take up with absorbent material.

After taking up the material dispose according to regulation.

**7. Handling and storage**

**Advice on safe handling**

Avoid formation of aerosols.

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

Open and handle container with care!

**Advice on protection against fire and explosion**

Keep away from sources of ignition - No smoking

**Requirements for storage rooms and vessels**

Keep in closed original container.

**Advice on storage compatibility**

Do not store together with animal feedstuffs.

Do not store together with food.

**Further information on storage conditions**

Storage temperature between 2°C to 40°C

**8. Exposure controls/personal protection**

**Ingredients with occupational exposure limits to be monitored**

CAS No	Name	Code	[mg/m3]	[ppm]	Remark
14807-96-6	Talc respirable dust	8 hours	1		EH40/2005

**Respiratory protection**

If ventilation insufficient, wear respiratory protection.

**Hand protection**

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]: natural rubber, 0,6mm; 480min; 60min;

Chemical protective gloves must be chosen carefully in view of their design and depending on the dependence on the concentration and amounts of dangerous goods used in the specific working tasks.

**Eye protection**

tightly fitting goggles  
protective shield

**Skin protection**

langärmelige Arbeitskleidung

**General protective measures**

Avoid contact with eyes and skin  
Do not inhale gases/vapours/aerosols.

**Hygiene measures**

At work do not eat, drink and smoke.

**9. Physical and chemical properties**

**Form**  
pasty

**Colour**  
black

**Odour**  
hardly noticeable

**Important health, safety and environmental information**

	Value	Temperature	at	Method	Remark
<b>pH value in delivery state</b>	ca. 7	25			1:1 in water
<b>Flash point</b>	> 200 °C			DIN 51758	Pensky-Martens Closed Cup
<b>Vapour pressure</b>	< 0,2 Pa	20 °C			
<b>Density</b>	3,28 g/cm <sup>3</sup>	25 °C			
<b>Solubility in water</b>		20 °C			more or less insoluble
<b>Viscosity dynamic</b>	190 - 200 Pa*s	50 °C			

**10. Stability and reactivity****Materials to avoid**

Reactions with strong acids and alkalis.  
Reactions with strong oxidising agents.

**Hazardous decomposition products**

Carbon monoxide and carbon dioxide.  
Toxic gases/vapours

**Thermal decomposition**

Remark No decomposition below 200°C.

**11. Toxicological information****Acute toxicity/Irritability/Sensitization**

	Value/Validation	Species	Method	Remark
<b>LD50 acute oral</b>	> 2000 mg/kg	rat		



	Value/Validation	Species	Method	Remark
<b>Irritability skin</b>	irritant	rabbit		
<b>Irritability eye</b>	irritant	rabbit eye		
<b>Skin sensitization</b>	sensitizing	Guinea pig		

**Experiences made from practice**

Sensitization through skin contact possible.

**Additional information**

Labelling in compliance with the assessment procedure specified in the EC guidelines 1999/45/EC.

**12. Ecological information**

**Data on elimination (persistence and degradability)**

	Elimination rate	Method of analysis	Method	Validation
<b>Biological degradability</b>				not readily degradable

**General regulation**

Do not allow uncontrolled leakage of product into the environment.  
Product is not allowed to be discharged into aquatic environment.

**13. Disposal considerations**

Waste code No.	Name of waste
07 02 08*	other still bottoms and reaction residues

Wastes marked with an asterisk are considered to be hazardous waste pursuant to Directive 91/689/EEC on hazardous waste.

**Recommendations for the product**

Remove in accordance with local official regulations.

**Recommendations for packaging**

Empty containers can be deposited after cleaning in accordance with the local waste regulations.

**14. Transport information**

**Transport/further information**

No dangerous goods as defined by the transport regulations - ADR/RID, IMDG, ICAO/IATA-DGR.

**15. Regulatory information**

VOC standard	
VOC content	0 %



Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

Printed 11.02.2011

Revision 10.02.2011 (GB) Version 6.0

**Plastic-Metal SF Resin (GB)**

---

## 16. Other information

### Recommend uses and restrictions

National and local regulations concerning chemicals shall be observed.

### Further information

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Listed in: EINECS; TSCA; DSL; AICS; KECI (KR); ENCS (JP).

### Wording of the R/H-phrases specified in chapter 3 (not the classification of the mixture!)

R 36/38 Irritating to eyes and skin.

R 43 May cause sensitisation by skin contact.

R 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R 52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.