



1. Identification of the substance/mixture and of the company/undertaking

Product identifier

Name of product Repair Stick Copper (GB)
Code-Nr. 105300

Manufacturer/distributor

WEICON GmbH & Co. KG
Königsberger Straße 255, DE-48157 Münster
Postbox 84 60, DE-48045 Münster
Phone ++49(0)251 / 9322 - 0, Fax ++49(0)251 / 9322-244
E-Mail : info@weicon.de
Internet : www.weicon.de

Advice

Abteilung Angebote, Verkauf, Export
Phone ++49(0)251 / 9322 - 0

Emergency advice

Giftnotruf Bonn: Bei Vergiftungen (in case of poisoning)
Phone ++49(0)228-19 240

Recommended intended purpose(s)

2-Component Epoxy Resins

2. Hazards identification

Classification according to 67/548/EEC or 1999/45/EC

Xi; R36/38

R43

R52/53

R-phrases

36/38

Irritating to eyes and skin.

43

May cause sensitisation by skin contact.

52/53

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Labelling according to 67/548/EEC or 1999/45/EC

Remarks for labelling

The product is classified and labelled in accordance with EC directives/German regulations on dangerous substances.

Xi Irritant

R-phrases

36/38

Irritating to eyes and skin.

43

May cause sensitisation by skin contact.

52/53

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

S-phrases

2

Keep out of the reach of children.

28

After contact with skin, wash immediately with plenty of water and soap.

37/39

Wear suitable gloves and eye/face protection.

46

If swallowed, seek medical advice immediately and show this container or label.

51

Use only in well-ventilated areas.



Hazardous ingredients for labeling

reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)

Special rules for supplemental label elements for certain mixtures

Contains epoxy constituents. See information supplied by the manufacturer.

3. Composition/information on ingredients

Description

2-component epoxy sticks

Hazardous ingredients

CAS No	EC No	Name	[% weight]	Classification according to 67/548/EEC
90-72-2	202-013-9	2,4,6-tris(dimethylaminomethyl)phenol	1 - 10	Xn R22; Xi R36/38
25068-38-6	500-033-5	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)	15 - 24	Xi R36/38; R43; N R51-53

4. First aid measures

General information

Remove contaminated soaked clothing immediately.

In case of inhalation

In the event of symptoms refer for medical treatment.

In case of skin contact

Do not use solvents or thinners.

In case of contact with skin wash off with water.

In case of eye contact

May cause superficial burns.

In case of contact with eyes rinse thoroughly with water.

Call for a doctor immediately.

In case of ingestion

Do not induce vomiting.

Call for a doctor immediately.

If swallowed by mistake drink plenty of water and seek medical treatment.

Rinse out mouth thoroughly with water.

Treatment (Advice to doctor)

In the event of pulmonary irritation treat initially with dexamethasone metered-dose aerosol.

5. Firefighting measures

Suitable extinguishing media

Foam

Dry fire-extinguishing substance

Carbon dioxide

water mist

Special hazards arising from the substance or mixture

Fire gas of organic material has to be classed invariably as respiratory poison.

Nitrogen oxides (NOx)

Carbon monoxide (CO)

Special protective equipment for fire-fighters

Use breathing apparatus with independent air supply.



Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

6. Accidental release measures

Personal precautions

Ensure adequate ventilation.
Remove persons to safety.
Use personal protective clothing.

Environmental precautions

Inform pollution control authorities if product gets into the sewerage systems or open waters.
Do not discharge into the drains or bodies of water..

Methods for cleaning up

Send in suitable containers for recovery or disposal.
Take up with absorbent material.

7. Handling and storage

Advice on safe handling

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

Advice on protection against fire and explosion

Pay attention to general rules of internal fire prevention.

Requirements for storage rooms and vessels

Keep in closed original container.

Further information on storage conditions

Protect from direct solar radiation.
Store container at cool and aired place.
Store in a dry place.
Protect from heat/overheating.

8. Exposure controls/personal protection

Respiratory protection

In case of insufficient ventilation or long-term effect use breathing apparatus.

Hand protection

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.
Glove material specification [make/type, thickness, permeation time/life, wetting resistance]: natural rubber, 0,6mm; 480min; 60min;
Chemical protective gloves must be chosen carefully in view of their design and depending on the dependence on the concentration and amounts of dangerous goods used in the specific working tasks.

Eye protection

safety goggles
Face shield

Skin protection

protective clothing

General protective measures

Avoid contact with eyes and skin
Do not inhale gases/vapours/aerosols.

Hygiene measures

At work do not eat, drink, smoke or take drugs.
Wash hands before breaks and after work.



14. Transport information

Transport/further information

No dangerous goods as defined by the transport regulations - ADR/RID, IMDG, ICAO/IATA-DGR.

15. Regulatory information

16. Other information

Recommendend uses and restrictions

National and local regulations concerning chemicals shall be observed.

Further information

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Wording of the R/H-phrases specified in chapter 3 (not the classification of the mixture!)

R 22 Harmful if swallowed.

R 36/38 Irritating to eyes and skin.

R 43 May cause sensitisation by skin contact.

R 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.