



1. Identification of the substance/mixture and of the company/undertaking

Product identifier

Name of product

Rust Loosener and Contact Spray (GB)
Code-Nr. 111500

Manufacturer/distributor

WEICON GmbH & Co. KG
Königsberger Straße 255, DE-48157 Münster
Postbox 84 60, DE-48045 Münster
Phone ++49(0)251 / 9322 - 0, Fax ++49(0)251 / 9322-244
E-Mail : info@weicon.de
Internet : www.weicon.de

Advice

Abteilung Angebote, Verkauf, Export
Phone ++49(0)251 / 9322 - 0

Emergency advice

Giftnotruf Bonn: Bei Vergiftungen (in case of poisoning)
Phone ++49(0)228-19 240

Recommended intended purpose(s)

Technical Aerosols

2. Hazards identification

Classification according to 67/548/EEC or 1999/45/EC

F+; R12

R52/53

R-phrases

12 Extremely flammable.

52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Labelling according to 67/548/EEC or 1999/45/EC

Remarks for labelling

The product is classified and labelled in accordance with EC directives/German regulations on dangerous substances.

F+ Extremely flammable

R-phrases

12 Extremely flammable.

52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

S-phrases

23 Do not breathe spray.

29 Do not empty into drains.

51 Use only in well-ventilated areas.

Special rules for supplemental label elements for certain mixtures

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material.

Without sufficient ventilation the formation of explosive vapour/air mixtures cannot be excluded. Keep away from sources of ignition - No smoking. Keep out of the reach of children.



Contents materials in accordance with Detergents Regulation (648/2004/EC)
15 - 30% aliphatic hydrocarbons
< 5% non-ionic surfactants

Information pertaining to special dangers for human and environment

In extensive use, formation of flammable / explosive vapour-air mixture is possible.

3. Composition/information on ingredients

Description

Mixture of active ingredients with propellant

Hazardous ingredients

CAS No	EC No	Name	[% weight]	Classification according to 67/548/EEC
95-38-5	202-414-9	2-(2-heptadec-8-enyl-2-imidazolin-1-yl) ethanol	0,1 - 0,99	C R34; Xn R22; N R50/53
64742-48-9		Naphtha (petroleum), hydrotreated heavy (NOTA P)	10 - 24,9	R10; Xn R65; R66
110-25-8	203-749-3	(Z)-N-methyl-N-(1-oxo-9-octadecenyl) glycine	0,1 - 0,99	XI R38-41; N R50/53
74-98-6	200-827-9	propane	10 - 24,9	F+ R12

4. First aid measures

General information

Remove contaminated soaked clothing immediately.

In case of inhalation

Ensure of fresh air.

In the event of symptoms refer for medical treatment.

In case of skin contact

In case of contact with skin wash off with water.

In case of eye contact

In case of contact with eyes rinse thoroughly with plenty of water and seek medical advice.

In case of ingestion

Do not induce vomiting.

Refer to medical treatment.

Physician's information / possible symptoms

The following symptoms may occur:

Anaesthetic state

Headache

5. Firefighting measures

Suitable extinguishing media

Foam

Dry powder

Carbon dioxide

water mist

Extinguishing media which must not be used for safety reasons

Full water jet

Special hazards arising from the substance or mixture

Danger of bursting

Fire gas of organic material has to be classed invariably as respiratory poison.



Special protective equipment for fire-fighters

Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

Additional information

Cool endangered containers with water spray jet.

6. Accidental release measures

Personal precautions

Ensure adequate ventilation.
Keep people away and stay on the upwind side.
Use personal protective clothing.

Environmental precautions

Do not discharge into the drains/surface waters/groundwater.

Methods for cleaning up

Take up with absorbent material.
After taking up the material dispose according to regulation.

7. Handling and storage

Advice on safe handling

Ventilate closed rooms at ground level.
Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking
Do not spray on a naked flame or any incandescent material.
Pressurized container.
Do not pierce or burn even after use.
The product is combustible.
Vapours can form an explosive mixture with air.
Avoid effect of heat.

Requirements for storage rooms and vessels

Keep in closed original container.
Adhere to administrative regulations relating to storage of compressed gas cylinders / containers.

Further information on storage conditions

Protect from heat and direct solar radiation.
Storage temperature may not exceed 50°C (=122°F).
Store container at cool and aired place.

8. Exposure controls/personal protection

Additional advice on system design

Sufficient ventilation and exhaustion.

Respiratory protection

In case of insufficient ventilation or long-term effect use breathing apparatus.
Short-term: filter apparatus, filter AX, otherwise environment-independent breathing apparatus.

Hand protection

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.
Glove material specification [make/type, thickness, permeation time/life, wetting resistance]: Nitrile rubber; 0,4mm; 480min;60min.
Chemical protective gloves must be chosen carefully in view of their design and depending on the dependence on the concentration and amounts of dangerous goods used in the specific working tasks.



Eye protection
safety goggles

Skin protection
protective clothing

General protective measures
Avoid contact with eyes and skin
Do not inhale gases/vapours/aerosols.

Hygiene measures
At work do not eat, drink and smoke.

9. Physical and chemical properties

Form aerosol	Colour various, depending on coloration	Odour characteristic
------------------------	---	--------------------------------

Important health, safety and environmental information

	Value	Temperature	at	Method	Remark
boiling point	187 °C				
Flash point	-97 °C				
Ignition temperature	236 °C				
Lower explosion limit	0,7 Vol-%				
Upper explosion limit	10,9 Vol-%				
Vapour pressure	3500 hPa	20 °C			
Density	0,803 g/ml	20 °C			
Solubility in water					immiscible
Solvent concentration	25,2 %				

Explosive properties

The product is considered non-explosive ; nevertheless explosive vapour/air mixtures can be generated .

10. Stability and reactivity

Conditions to avoid
Keep away from heat.
Formation of inflammable vapour-air mixtures.

Hazardous decomposition products
Carbon monoxide and carbon dioxide.

Thermal decomposition

Remark No decomposition if used as directed.



11. Toxicological information

Acute toxicity/Irritability/Sensitization

	Value/Validation	Species	Method	Remark
Irritability skin	non-irritant			
Irritability eye	non-irritant			
Skin sensitization	non-sensitizing			

Additional information

Labelling in compliance with the assessment procedure specified in the EC guidelines 1999/45/EC.

12. Ecological information

General regulation

Even in the event of low quantities penetration into the underground drinking water is contaminated.
Do not allow uncontrolled leakage of product into the environment.
Product is not allowed to be discharged into aquatic environment.

13. Disposal considerations

Waste code No.	Name of waste
15 01 10*	packaging containing residues of or contaminated by dangerous substances

Wastes marked with an asterisk are considered to be hazardous waste pursuant to Directive 91/689/EEC on hazardous waste.

Recommendations for the product

Remove in accordance with local official regulations.

Recommendations for packaging

Dispose of according to the local waste regulations.

Recommended cleansing agent

E.g white spirit.

14. Transport information

Land and inland navigation transport ADR/RID

UN 1950 AEROSOLS, 2.1, (D), Classification code: 5F
transport in "limited quantities" according to 3.4 ADR LQ2 is possible

Marine transport IMDG

UN 1950 AEROSOLS, 2.1

Air transport ICAO/IATA-DGR

UN 1950 Aerosols, flammable, 2.1

Transport/further information

24h EMERGENCY CONTACT (TRANSPORT) +49(0)178 433 7434 (Consultank Lutz Harder GmbH)



15. Regulatory information

VOC standard
VOC value 202,4 g/L

16. Other information

Recommendend uses and restrictions

National and local regulations concerning chemicals shall be observed.

Further information

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Danish MAL Code 5-6

VOC-CH 25,20 %

Wording of the R/H-phrases specified in chapter 3 (not the classification of the mixture!)

R 10 Flammable.

R 12 Extremely flammable.

R 22 Harmful if swallowed.

R 34 Causes burns.

R 38 Irritating to skin.

R 41 Risk of serious damage to eyes.

R 50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R 65 Harmful: may cause lung damage if swallowed.

R 66 Repeated exposure may cause skin dryness or cracking.