



## Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

Printed 11.02.2011

Revision 10.02.2011 (GB) Version 6.0

### W44T Turbo-Power liquid (GB)

## 1. Identification of the substance/mixture and of the company/undertaking

### Product identifier

#### Name of product

W44T Turbo-Power liquid (GB)  
Code-Nr. 152510

#### Manufacturer/distributor

WEICON GmbH & Co. KG  
Königsberger Straße 255, DE-48157 Münster  
Postbox 84 60, DE-48045 Münster  
Phone ++49(0)251 / 9322 - 0, Fax ++49(0)251 / 9322-244  
E-Mail : info@weicon.de  
Internet : www.weicon.de

#### Advice

Abteilung Angebote, Verkauf, Export  
Phone ++49(0)251 / 9322 - 0

#### Emergency advice

Giftnotruf Bonn: Bei Vergiftungen (in case of poisoning)  
Phone ++49(0)228-19 240

#### Recommended intended purpose(s)

Technical Liquids

## 2. Hazards identification

### Classification according to 67/548/EEC or 1999/45/EC

R10

N; R51/53

Xn; R65

R66

R67

#### R-phrases

10

Flammable.

51/53

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

65

Harmful: may cause lung damage if swallowed.

66

Repeated exposure may cause skin dryness or cracking.

67

Vapours may cause drowsiness and dizziness.

### Labelling according to 67/548/EEC or 1999/45/EC

#### Remarks for labelling

The product is classified and labelled in accordance with EC directives.

Xn Harmful

N Dangerous for the environment

#### R-phrases

10

Flammable.

51/53

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

65

Harmful: may cause lung damage if swallowed.

66

Repeated exposure may cause skin dryness or cracking.

67

Vapours may cause drowsiness and dizziness.

**S-phrases**

|       |  |
|-------|--|
| 16    | Keep away from sources of ignition - No smoking.   |
| 2     | Keep out of the reach of children.   |
| 23    | Do not breathe vapour.   |
| 29/56 | Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point. |
| 46    | If swallowed, seek medical advice immediately and show this container or label.                                      |
| 62    | If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.              |
| 9     | Keep container in a well-ventilated place.   |

**Hazardous ingredients for labeling**

Naphtha (petroleum), hydrotreated heavy (NOTA P)

**3. Composition/information on ingredients****Hazardous ingredients**

| CAS No     | EC No     | Name  | [% weight] | Classification according to 67/548/EEC |
|------------|-----------|---|------------|--|
| 64742-82-1 | 265-185-4 | Naphtha (petroleum), hydrodesulfurized full-range; Low boiling point hydrogen treated naphtha | > 60       | Xn R65; R66-67; R10; N R51/53          |

**4. First aid measures****General information**

Remove contaminated soaked clothing immediately.

**In case of inhalation**

Remove the casualty into fresh air and keep him immobile.

In the event of symptoms refer for medical treatment.

**In case of skin contact**

In case of contact with skin wash off with soap and water.

Consult a doctor if skin irritation persists.

**In case of eye contact**

In case of contact with eyes rinse with plenty of water carefully. In the event of persistent symptoms seek medical treatment.

**In case of ingestion**

If swallowed or in case of vomiting, danger of infiltration into the lungs (danger of aspiration).

Do not induce vomiting.

Medical treatment.

Rinse out mouth thoroughly with water.

**5. Firefighting measures****Suitable extinguishing media**

Foam

Dry powder

Carbon dioxide

**Extinguishing media which must not be used for safety reasons**

water

**Special hazards arising from the substance or mixture**

Fire gas of organic material has to be classed invariably as respiratory poison.

**Special protective equipment for fire-fighters**

Use breathing apparatus with independent air supply.



---

Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

**Additional information**

Cool endangered containers with water spray jet.

---

## 6. Accidental release measures

**Personal precautions**

Ensure adequate ventilation.

Keep away sources of ignition.

**Environmental precautions**

Do not discharge into the drains or bodies of water..

**Methods for cleaning up**

Take up residues with suitable absorbent materials.

After taking up the material dispose according to regulation.

---

## 7. Handling and storage

**Advice on safe handling**

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

**Advice on protection against fire and explosion**

Keep away from sources of ignition - No smoking

The product is combustible.

**Requirements for storage rooms and vessels**

Keep in closed original container.

**Further information on storage conditions**

Protect from direct solar radiation.

Storage temperature may not exceed 50°C (=122°F).

Store container at cool and aired place.

Store in a dry place.

---

## 8. Exposure controls/personal protection

**Respiratory protection**

If ventilation insufficient, wear respiratory protection.

**Hand protection**

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]:: Nitrile rubber; 0,4mm; 480min;60min.

**Eye protection**

safety goggles

**Skin protection**

Light protective clothing.

**General protective measures**

Do not inhale gases/vapours/aerosols.

Avoid contact with the eyes.

**Hygiene measures**

Cloths contaminated with product should not be kept in trouser pockets.

At work do not eat, drink and smoke.

Wash hands before breaks and after work.





---

**General regulation**

Do not allow uncontrolled leakage of product into the environment.

Product is not allowed to be discharged into aquatic environment.

---

**13. Disposal considerations**

**Waste code No.**

13 02 05\*

15 01 10\*

**Name of waste**

mineral-based non-chlorinated engine, gear and lubricating oils

packaging containing residues of or contaminated by dangerous substances

Wastes marked with an asterisk are considered to be hazardous waste pursuant to Directive 91/689/EEC on hazardous waste.

**Recommendations for the product**

Remove in accordance with local official regulations.

**Recommendations for packaging**

Dispose of according to the local waste regulations.

---

**14. Transport information**

**Land and inland navigation transport ADR/RID**

UN 1268 PETROLEUM DISTILLATES, N.O.S. (NAPHTHA (ERDÖL)), 3, III, (D/E), Classification code: F1

**Marine transport IMDG**

UN 1268 PETROLEUM DISTILLATES, N.O.S. (NAPHTHA (PETROLEUM)), 3, III, MARINE POLLUTANT

**Air transport ICAO/IATA-DGR**

UN 1268 Petroleum distillates, n.o.s. (NAPHTHA (PETROLEUM)), 3, III

**Transport/further information**

24h EMERGENCY CONTACT (TRANSPORT) +49(0)178 433 7434 (Consultank Lutz Harder GmbH)

---

**15. Regulatory information**

**VOC standard**

**VOC content**

57,6 %

**VOC value**

576 g/L

---

**16. Other information**

**Recommend uses and restrictions**

National and local regulations concerning chemicals shall be observed.

**Further information**

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

**Wording of the R/H-phrases specified in chapter 3 (not the classification of the mixture!)**

R 10 Flammable.

R 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R 65 Harmful: may cause lung damage if swallowed.

R 66 Repeated exposure may cause skin dryness or cracking.

R 67 Vapours may cause drowsiness and dizziness.