

Weicon GmbH

Revision date: 24.08.2010

Revision no.:

1,00

Anti-Seize ASW 200 PR, "High Tech", spray can

7619-0260

**1. Product and Company Identification****Commercial product name**

Anti-Seize ASW 200 PR, "High Tech", spray can

**Further trade names**

261010

**Chemical characterization** ( Mixture )**Company/undertaking identification****Manufacturer**

Weicon GmbH

Königsberger Straße 255

D-48157 Münster

Telephone: +49 (0) 251 9322 - 0

Telefax: +49 (0) 251 9322 - 244

e-mail: info@weicon.de

Internet: www.weicon.de

Responsible for the safety data sheet: sds@gbk-ingelheim.de

**2. Hazards Identification****Route(s) of Entry**

Skin and eye contact, inhalation and ingestion.

**Signs and Symptoms of Exposure**

DANGER!

Extremely flammable.

Contents under pressure.

Risk of serious damage to eyes.

OSHA Hazard Communication: This material is considered hazardous by the OSHA Hazard Communication Standard 29CFR 1910.1200.

Carcinogenicity (NTP): Not listed

Carcinogenicity (IARC): Not listed

Carcinogenicity (OSHA): Not listed

**3. Composition/Information on Ingredients****Hazardous components**

CAS No.	Components	Quantity
1305-62-0	Calcium dihydroxide	<15 %
74-98-6	propane	<2 %
106-97-8	butane	<2 %

**4. First Aid Measures****General information**

Remove contaminated soaked clothing immediately.

**After inhalation**

Move to fresh air in case of accidental inhalation of vapours.

In the event of symptoms refer for medical treatment.

**After contact with skin**

Wash off with soap and plenty of water.

Consult a doctor if skin irritation persists.

Weicon GmbH

Revision date: 24.08.2010

Revision no.:

1,00

Anti-Seize ASW 200 PR, "High Tech", spray can

7619-0260

---

#### **After contact with eyes**

In case of contact with eyes rinse with plenty of water carefully. In the event of persistent symptoms seek medical treatment.

If eye irritation persists, consult a specialist.

#### **After ingestion**

Do not induce vomiting.

Summon a doctor immediately.

---

### **5. Fire Fighting Measures**

#### **Suitable extinguishing media**

Foam

Dry powder

Carbon dioxide (CO<sub>2</sub>)

Water spray jet

#### **Special hazards arising from the chemical**

Fire may produce:

Carbon monoxide and carbon dioxide.

#### **Protective equipment and precautions for firefighters**

Use breathing apparatus with independent air supply.

#### **Additional information**

Heating will cause pressure rise with risk of bursting.

Cool containers at risk with water spray jet.

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

---

### **6. Accidental Release Measures**

#### **Personal precautions**

Keep away sources of ignition.

In case of vapour formation use respirator.

Use only explosion-proof equipment.

Ensure adequate ventilation.

Use personal protective clothing.

#### **Environmental precautions**

Do not discharge into the drains/surface waters/groundwater.

Do not discharge into the subsoil/soil.

#### **Methods for cleaning up/taking up**

Take up with absorbent material.

Shovel into suitable container for disposal.

#### **Additional information**

High risk of slipping due to leakage/spillage of product.

---

### **7. Handling and Storage**

#### **Handling**

##### **Advice on safe handling**

Ensure adequate ventilation.

Avoid contact with skin, eyes and clothing.

The product is combustible.

Vapours can form an explosive mixture with air.

##### **Advice on protection against fire and explosion**

Keep away from sources of ignition - No smoking.

Do not spray on a naked flame or any other incandescent material.

Heating will cause pressure rise with risk of bursting.

Weicon GmbH

Revision date: 24.08.2010

Revision no.:

1,00

Anti-Seize ASW 200 PR, "High Tech", spray can

7619-0260

**Further information on handling**

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

**Storage****Requirements for storage rooms and vessels**

Protect from heat and direct solar radiation.

Keep containers tightly closed in a cool, well-ventilated place.

Recommended storage temperature: room temperature.

**Advice on storage compatibility**

Incompatible with oxidizing agents.

**Further information on storage conditions**

Keep away from food, drink and animal feeding stuffs.

**8. Exposure Controls/Personal Protection****Exposure limit values****Exposure limits**

CAS No.	Components	ppm	mg/m <sup>3</sup>	fib/cc	Category	Origin
106-97-8	Butane	1000			TWA (8 h)	TLV
		-	-	-	STEL (15 min)	TLV
		-	-	-	Peak	TLV
1305-62-0	Calcium hydroxide	-	5		TWA (8 h)	REL
	Calcium hydroxide Respirable fraction	-	5		TWA (8 h)	REL
74-98-6	Propane	1000	1800		TWA (8 h)	REL
		1000	1800		TWA (8 h)	REL
		1000			TWA (8 h)	TLV
		-	-	-	STEL (15 min)	TLV
		-	-	-	Peak	TLV
106-97-8	n-Butane	800	1900		TWA (8 h)	REL

**Additional advice on limit values**

Aliphatic hydrocarbon gases (propane/butane/Alkane C1-C4) have workplace limits of 1000 ppm (TWA-ACGIH).

**Occupational exposure controls**

Do not inhale gases/vapours/aerosols.

**Protective and hygiene measures**

Ensure adequate ventilation, especially in confined areas.

Wash hands before breaks and immediately after handling the product.

At work do not eat, drink, smoke or take drugs.

Take off immediately all contaminated clothing.

Avoid contact with eyes, skin or mucous membrane.

**Respiratory protection**

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type AX).

**Hand protection**

Protective gloves resistant to chemicals made of nitrile, Minimum coat thickness 0.4 mm, Permeation resistance (wear duration) approx. 480 minutes, i.e. protective glove <Camatril Velours 730> made by www.kcl.de.

This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.

Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Weicon GmbH

Revision date: 24.08.2010

Revision no.:

1,00

Anti-Seize ASW 200 PR, "High Tech", spray can

7619-0260

**Eye protection**

Safety goggles with side protection

**Skin protection**

Protective clothing

**9. Physical and Chemical Properties****Appearance**

Form:	Aerosol
Color:	White
Odor:	Odourless

**Important health, safety and environmental information**

Test method

**Changes in the physical state**

Flash point: &lt; 0 °C

**Explosive properties**

"The product is considered non-explosive; nevertheless explosive vapour/air mixture can be generated."

Lower explosion limits: n.d.

Upper explosion limits:

Vapour pressure: 5,5 hPa  
(at 20 °C)Density (at 20 °C): 1,4 g/cm<sup>3</sup> DIN 51757Water solubility: Insoluble  
(at 20 °C)**10. Stability and Reactivity****Stability**

Stable

**Conditions to avoid**

Fire or intense heat may cause violent rupture of packages.

Keep away from heat and sources of ignition.

**Materials to avoid**

Strong oxidizing agents

Reactions with strong acids.

**Hazardous decomposition products**

Carbon monoxide and carbon dioxide.

**Possibility of Hazardous Reactions**

Will not occur

**Additional information**

No decomposition if stored and applied as directed.

**11. Toxicological Information****Acute toxicity**

Description of possible hazards to health effects is based on experience and/or toxicological characteristics of several components.

Harmful by inhalation.

**Specific effects in experiment on an animal**

Acute oral toxicity not determinable.

**Corrosive and irritant effects**

Irritant to eyes.

Risk of strong eye injuries.

Weicon GmbH

Revision date: 24.08.2010

Revision no.:

1,00

Anti-Seize ASW 200 PR, "High Tech", spray can

7619-0260

Irritates mucous membranes.

**Sensitising effects**

Skin sensitization, remark : Non-sensitizing

**Empirical data on effects on humans**

Harmful by inhalation.

**12. Ecological Information****Ecotoxicity**

Ecological data are not available.

**Further information**

Do not discharge product unmonitored into the environment.

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**13. Disposal Considerations****Advice on disposal**

Where possible recycling is preferred to disposal.

Remove in accordance with local official regulations. If recycling is not practicable, dispose of in compliance with local regulations.

**Contaminated packaging**

Offer empty spray cans to an established disposal company.

**14. Transport Information****US DOT 49 CFR 172.101****Proper shipping name**

AEROSOLS

ID Number:	1950
Hazard Class or Division:	2.1
Packing group:	-
Label:	2.1

**Land transport (ADR/RID)**

UN number:	1950
ADR/RID class:	2
Warning plate	
Hazard-no.:	-
Hazard label:	2.1



ADR/RID packing group:	-
------------------------	---

**Description of the goods**

AEROSOLS

**Other applicable information**

LQ 2: combination packaging: 1 l / 30 kg (total gross mass); trays: 1 l / 20 kg (total gross mass).

Additional label with symbol "fish and tree" according to subsection 5.2.1.8.3. ADR for single packagings and inner packagings with &gt; 5 kg or 5 L, transition period ends 31.12.2010.

**Marine transport**

UN number:	1950
IMDG code:	2
Marine pollutant:	No
Hazard label:	2.1

Weicon GmbH

Revision date: 24.08.2010

Revision no.:

1,00

Anti-Seize ASW 200 PR, "High Tech", spray can

7619-0260



IMDG packing group: -

EmS:

F-D; S-U

**Description of the goods**

AEROSOLS

**Other applicable information**

Limited quantities (chapter 3.4): combination packaging: 1 l / 30 kg (total gross mass); trays: 1 l / 20 kg (total gross mass)

**Air transport**

UN/ID number:

1950

ICAO/IATA-DGR:

2.1

Hazard label:

2.1



ICAO packing group: -

IATA-packing instructions - Passenger:

203

IATA-max. quantity - Passenger:

75 kg

IATA-packing instructions - Cargo:

203

IATA-max. quantity - Cargo:

150 kg

**Description of the goods**

AEROSOLS FLAMMABLE

**15. Regulatory Information****U.S. Regulations****National Inventory TSCA**

All of the components are listed on the TSCA inventory.

**SARA**

To the best of our knowledge this product contains no toxic chemicals subject to the supplier notification requirements of Section 313 of the Superfund Amendments and Reauthorization Act (SARA/EPCRA) and the requirements of 40 CFR Part 372.

**16. Other Information****Hazardous Materials Information Label (HMIS)**

Health: 1

Flammability: 4

Physical Hazard: 0

**NFPA Hazard Ratings**

Health: 1

Flammability: 4

Reactivity: 0

Unique Hazard:

**Other data**

Data of sections 4 to 8, as well as 10 to 12, do not necessarily refer to the use and the regular handling of the product (in this sense consult package leaflet and expert information), but to release of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product (s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal

**Material Safety Data Sheet according to ANSI Z400.1-2004**



Weicon GmbH

Revision date: 24.08.2010

Revision no.:

1,00

Anti-Seize ASW 200 PR, "High Tech", spray can

7619-0260

---

warranty regulations.

"(n.a. = not applicable; n.d. = not determined)"

---

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*