

New



Workshop Cleaner

Workshop Cleaner cleans and degreases all metals, plastics, rubbers, glass, ceramics and wood. Powerfully removes grease, oil, resin, soot, wax, nicotine, insect dirt, bitumen and tar splashes. Workshop Cleaner is free of solvents and phosphates, compatible with oil separators (ÖNORM B5105) and biodegradable according to EU regulations. Workshop Cleaner is highly concentrated and can be diluted with water on a ratio of 1:40 (max).

Areas of application:

- Machines and tools of all types
- Workshop equipment, e.g. workshop benches, shelves, roller doors, industrial floors
- Vehicles, e.g. forklift trucks, low lift platform trucks, lorries, industrial trucks
- Engine parts, e.g. oil sumps, valve covers, starting motor, dynamos

Workshop Cleaner contains selected low-foam tensides and can also be used in high pressure cleaners, parts' washing machines and spray appliances (e.g. pump dispenser WPS 1500)* in addition to being used for manual cleaning. Special contents provide a temporary corrosion protection.

| | Recommended application concentration | | | | |
|--|---------------------------------------|------|------|------|------|
| | undiluted | 1:10 | 1:20 | 1:30 | 1:40 |
| Aluminium parts | | | | | • |
| Inspection pits | | • | | | |
| Grease, soot, bitumen and tar splashes | • | | | | |
| Chromium, stainless steel and plastic | | | | • | |
| Diesel residue | • | | | | |
| Insect dirt | | • | | | |
| Industrial floors, forklift trucks | | | | • | |
| Hard floors | | • | | | |
| Lorries (also tarred canvases) | | • | | | |
| Machines, engines, oil/oil residues | | • | | | |
| Repair parts | | | | | • |
| Steel degreasing | | | • | | |
| Workshop equipment, | | | | • | |
| Machine tools | | | | • | |

Instructions for use:

Apply Workshop Cleaner generously to the parts that need to be cleaned, allow it to soak in and wipe it off with a clean cloth. Repeat this action in the event of stubborn stains. The cleaning process can be shortened by warming up the product (max. +90°C). Particularly coarse dirt can be removed more simply in this way. Do not apply it undiluted to aluminium or zinc coatings (alkaline, concentrated pH value approx. 12). Protect against frost.

* Not suitable for processing with the WSD 400 compressed air can.

Packaging:

| | | |
|------|------|--------------------|
| 5 l | Bulk | Art.-No.: 15205005 |
| 10 l | Bulk | Art.-No.: 15205010 |
| 30 l | Bulk | Art.-No.: 15205030 |

WEICON GmbH & Co. KG

Königsberger Str. 255 • DE-48157 Münster
P.O.B. 84 60 • DE-48045 Münster

Tel. +49 (0) 251 / 93 22-0
Fax +49 (0) 251 / 93 22-44
Fax +49 (0) 251 / 93 22-33 Export

www.weicon.de
eMail: info@weicon.de
Tel. 0700/weiconde

Distributed by:



Reinigen von Werkstattböden
Cleaning of workshop floors



Reinigung von Werkzeugmaschinen
Cleaning of machine tools



Reinigen von Verkleidungen, auch an Schaltanlagen
Cleaning of cases, e.g. switchboard plants



Reinigen von Streifenvorhängen aus Kunststoff
Cleaning of plastic curtains



Reinigen und Entfetten von Motorenteilen in Teile-Waschmaschinen
Cleaning and degreasing of engine parts in parts' washing machines

Any product specifications and recommendations given herein must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do warrant the continuously high quality of our products being free from defects in accordance with and subject to our General Sales Conditions. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are to be carried out.